

SAFETY TAGS---"DANGER", "NOTICE", "CAUTION"



- Safety tags are placed on equipment
 - to isolate a hazardous energy source for personnel protection
 - to identify unsafe, damaged, or deficient systems, components, or equipment
 - to prevent improper operation when a component, system, or portion of a system is isolated or in an abnormal condition
- To prevent potential safety hazards and injury
 - Use the correct tag for the intended purpose
 - Record all of the required information
 - Do not remove the tag without contacting the authorized person (installer)

“DANGER” Tags

- Indicate an imminently hazardous situation which, if not avoided, will result in death or serious injury. Danger tags are used for "Lockout / Tagout" of energy isolation devices. Danger tags are to be used for “ LO/TO” ONLY when safing a circuit or system so work can be performed on the system safely.

Front

Front view details:
TAG # 37120
PPPL LOCKOUT TAGOUT SYSTEM
! DANGER
DO NOT USE, MOVE OR OPERATE
DO NOT REMOVE THIS TAG
This tag is attached to _____
AUTHORIZED PERSON APPLYING TAG
Name: _____
Co./Dept.: _____
Date: _____
Phone #: _____ Pager #: _____
STUB TO BE KEPT BY AUTHORIZED EMPLOYEE OR KEPT IN A LOCK BOX
Name: _____
Date: _____ TAG #: 37120
This Tag Has Been Attached To _____

Back view details:
PPPL LOCKOUT TAGOUT SYSTEM
! DANGER
DO NOT USE, MOVE OR OPERATE
DO NOT REMOVE THIS TAG
This tag indicates an imminently hazardous situation which, if not avoided, will result in death or serious injury. Unauthorized removal or tampering with this tagged equipment is cause for dismissal. A life is on the line!
TASK DESCRIPTION OR REASON FOR TAG

Reason For Tag: _____
Location: _____

Back

For More Information

- PPPL ESH-001 Use of Safety, Accident Prevention, and Equipment Protection tags
- PPPL ESH-016 Control of Hazardous Energy Sources (LO/TO)