






INSPECTION DATA CHECKLIST

Workorder: 65709/3-0 Sub:1 Op:132

Revision: 07/27/06 8:45

Part: SE141-114 - MODULAR COIL WINDING FORM TYPE-A - PRODUCTION MODULAR COIL WINDING FORM TYPE-A

Drawing ID: SE141-114 Rev: 7			INSPECTION INSTRUCTIONS			RESULTS		INSPECTED BY		
SHEET	ZONE	CHARACTERISTIC	GAGE/EQUIP	BY	SAMPLE	SER#	DATA/REMARKS	INSP	VERFD	AUDIT
1* (10)	F3	NOTE 14 - BACK SPOTFACE ALL THRU HOLES TO MINIMUM CLEAN UP.		QA		VISUAL	ACCEPT	339-E.RO 07-27-06		
1* (20)	E8	FLANGE PROFILE +/- .25 IN THIS AREA	CMM	QA		00064	.0045	339-E.RO 07-27-06		
1* (30)	D8		CMM	QA		00064	.004	339-E.RO 07-27-06		
1* (40)	D8	54.20 ± .03	CMM	QA		00064	54.200	339-E.RO 07-27-06		
1* (50)	C8	54.20 ± .03	CMM	QA		00064	54.199	339-E.RO 07-27-06		
1* (60)	B8		CMM	QA		00064	.002	339-E.RO 07-27-06		
1* (70)	D5		CMM	QA		00064	.004	339-E.RO 07-27-06		
1* (80)	D5	48.50 ± .03	CMM	QA		00064	48.480	339-E.RO 07-27-06		
1* (90)	C5	48.50 ± .03	CMM	QA		00064	48.508	339-E.RO 07-27-06		
1* (100)	B5		CMM	QA		00064	.009	339-E.RO 07-27-06		
1* (110)	D4	VERIFY PART MARKING: MAJOR TOOL SE141-114 A(casting number) (weight) LBS.	CMM	QA		00064	ACCEPT	339-E.RO 07-27-06		
1* (120)	D4	RECORD WEIGHT	CMM	QA		00064	5440	339-E.RO 07-27-06		
1*	D3		CMM	QA		00064	-.056 TO .457 [N/C:	339-E.RO		

* To Far Right Indicates Data Package Requirement

NOTE: the recording of false, fictitious, or fraudulent statements or entries on this document may be punished as a felony under federal statutes including federal law, title 18, chapter 47.

INSPECTION DATA CHECKLIST

(130)		OUTER AS CAST SURFACES					20201-Doc:NC20201]	07-27-06			*
2* (140)	F8	2 X .40	CMM	QA		00064	0.39 TO 0.41	339-E.RO 07-27-06			A *
2* (150)	F8	4 X .03 X 45	CALIPER	QA		J-707	.010 TO .040 [N/C:2 0201-Doc:NC20201]	533-B.CL 07-26-06			R *
2* (160)	G6	2 X R.187 +.025 / -.005	PIN GAGE	QA		J-651-2	.184 TO .207	533-B.CL 07-26-06			A *
2* (170)	G5	 P TO M	CMM	QA		00064	.0149 TO .076	339-E.RO 07-27-06			A *
2* (190)	F5	 M TO M1	CMM	QA		00064	-.020 TO .017 [N/C: 20201-Doc:NC20201]	339-E.RO 07-27-06			R *
2* (200)	E5	 M1 TO N1	CMM	QA		00064	-.011 TO .022	339-E.RO 07-27-06			A *
2* (210)	G3	 Q TO N	CMM	QA		00064	-.007 TO .094	339-E.RO 07-27-06			A *
2* (220)	F3	DATUM E SIDE VERIFY SHELL INTERSECT CLEARANCE USING GAGE MTMFX-3473		QA		MTMFX-3473	ACCEPT	533-B.CL 07-26-06			A *
2* (230)	F3	 N TO N1	CMM	QA		00064	-.024 TO .015 [N/C: 20201-Doc:NC20201]	339-E.RO 07-27-06			R *
2* (240)	B4	2 X .06/.09 X 45	CALIPER	QA		J-707	.030 TO .068 [N/C:20 201-Doc:NC20201]	533-B.CL 07-26-06			R *
2* (250)	B5	Ø .375-16 UNC ▽ .750 +.1 -0 96 X	THREAD PLUG GAGE	QA	100%	A-444	ACCEPT [N/C:20201-D oc:NC20201]	242-M.G 07-27-06			A *
2* (260)	B5	 Ø.625 ▽ .188	DEPTH MICROMETE PIN GAGE	QA		J-1024 J-652-3	.620 TO .621 DIA. DEPTH .183 TO .191 [N/C:20201-Doc:NC20 201]	242-M.G 07-27-06			A *
2* (270)	B5	 .375-16 HOLES	CMM	QA		00064	.0052 TO .072 [N/C: 20201-Doc:NC20201]	339-E.RO 07-27-06			R *
3* (280)	H3	 DATUM E FLANGE	CMM	QA		00064	.011 [N/C:20201-Doc :NC20201]	339-E.RO 07-27-06			R *
3*	H4	√ ¹²⁵	PROFILOMETER	QA		J-1109	20 TO 100	533-B.CL			A

* To Far Right Indicates Data Package Requirement

NOTE: the recording of false, fictitious, or fraudulent statements or entries on this document may be punished as a felony under federal statutes including federal law, title 18, chapter 47.

INSPECTION DATA CHECKLIST

(285)		DATUM E FLANGE						07-26-06		*
3* (290)	F2	 .01 DATUM D FLANGE	CMM	QA		00064	.007	339-E.RO 07-27-06		A *
3* (295)	F3	 .125 DATUM D FLANGE	PROFILOMETER	QA		J-1109	40 TO 125 [N/C:2020 1-Doc:NC20201]	242-M.G 07-27-06		A *
3* (300)	E4	Ø2.50 THRU	CALIPER	QA		J-707	2.497	533-B.CL 07-26-06		A *
3* (310)	F4	 .060 A B C Ø2.50	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06		A *
3* (320)	C7	8X Ø1-8UNC ∇ 2	THREAD PLUG GAGE	QA		A-71	ACCEPT	533-B.CL 07-26-06		A *
3* (330)	C7	 .010 A B C 8X Ø1-8 UNC	CMM	QA		00064	.001 TO .025 [N/C:2 0201-Doc:NC20201]	339-E.RO 07-27-06		R *
3* (340)	D5	8X Ø1-8UNC THRU	THREAD PLUG GAGE	QA		A-71	ACCEPT	533-B.CL 07-26-06		A *
3* (350)	D5	 .010 A B C 8X Ø1-8 UNC	CMM	QA		00064	.007 TO .048 [N/C:2 0201-Doc:NC20201]	339-E.RO 07-27-06		R *
3* (360)	D3	Ø2.50 THRU	CALIPER	QA		J-707	2.499	533-B.CL 07-26-06		A *
3* (370)	D3	 .060 A B C Ø2.5	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06		A *
3* (380)	D1	40.90	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06		A *
4* (390)	H6	 .002 A B C Ø2.000-2.001 ∇ 0.990-1.000	DIAL BORE GAGE DEPTH MICROMETE	QA		J-1400 J-1024	2.000 DEPTH .998	339-E.RO 07-27-06		A *
4* (400)	F4	Ø1.375-6UNC THRU	THREAD PLUG GAGE	QA		A-375	ACCEPT	533-B.CL 07-26-06		A *
4* (410)	F4	 .06 M A D Ø1.375-6	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06		A *
4* (420)	D4 &	Ø1.885 \pm .003 THRU	DIAL BORE GAGE	QA		J-1400	1.883 TO 1.886	533-B.CL 07-26-06		A *
4* (430)	D4 &	 .06 M A D Ø1.885	CMM	QA		00064	.0036 TO .044	339-E.RO 07-27-06		A *
4*	B6	3X Ø1.5	CALIPER	QA		J-1103	1.503 TO 1.505	533-B.CL		A

* To Far Right Indicates Data Package Requirement

NOTE: the recording of false, fictitious, or fraudulent statements or entries on this document may be punished as a felony under federal statutes including federal law, title 18, chapter 47.

INSPECTION DATA CHECKLIST

(440)								07-26-06		*
4* (450)	B6	$\Phi .06$ M A D 3X Ø1.5	CMM	QA		00064	.004 TO .018	339-E.RO 07-27-06		A *
4* (460)	A4	6X .25-20 UNC ∇ .5 .5 X 82° CHAMFER	THREAD PLUG GAGE	QA		A-726	ACCEPT	533-B.CL 07-26-06		A *
5* (470)	D8/D6	Ø1.885 ±.003	CMM	QA		00064	1.8855 ,1.8858, 1 H OLE 2.0515" [N/C:20 124-Doc:NC20124]	242-M.G 07-27-06		R *
5* (480)	D8/D6	$\Phi \varnothing .06$ N A E Ø1.885	CMM	QA		00064	.013 TO .053	339-E.RO 07-27-06		A *
5* (490)	F8	Ø1.375-6UNC THRU	THREAD PLUG GAGE	QA		A-375	ACCEPT	495-D.CO 07-26-06		A *
5* (500)	F8	$\Phi \varnothing .06$ N A E Ø1.375-6 UNC	CMM	QA		00064	.048	339-E.RO 07-27-06		A *
5* (510)	F6	8X 1/4 -20 UNC-2B	THREAD PLUG GAGE	QA		A-375	ACCEPT 23 PLACES	495-D.CO 07-26-06		A *
5* (520)	D6	3X Ø1.5 ∇ 2.33	CALIPER DEPTH MICROMETE	QA		J-1103 J-1024	1.503 TO 1.505 D EPTH 2.337	533-B.CL 07-26-06		A *
5* (530)	D6	$\Phi \varnothing .06$ N A E 3X Ø1.5	CMM	QA		00064	.002 TO .032	339-E.RO 07-27-06		A *
5* (540)	B3	6X .25 - 20 UNC ∇ .6 Ø.5 X 82° CHAMFER	THREAD PLUG GAGE	QA		A-726	ACCEPT	533-B.CL 07-26-06		A *
6* (550)	H7	6.00	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06		A *
6* (560)	H7	1.00	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06		A *
6* (570)	G8	6.70	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06		A *
6* (600)	F8	6.70	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06		A *
6* (610)	E7	5.75	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06		A *

* To Far Right Indicates Data Package Requirement

NOTE: the recording of false, fictitious, or fraudulent statements or entries on this document may be punished as a felony under federal statutes including federal law, title 18, chapter 47.



INSPECTION DATA CHECKLIST

6* (620)	E7	1.00	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06			A *
6* (630)	E6	4X Ø1.00	PIN GAGE	QA		J-921	.993 TO 1.00	533-B.CL 07-26-06			A *
6* (640)	C5	2X .88 - 1.13	CALIPER	QA		J-707	1.120 TO 1.130	533-B.CL 07-26-06			A *
6* (650)	F5	.06-.09 X 45° TYP	CALIPER	QA		J-707	.080	533-B.CL 07-26-06			A *
7* (660)	G2	19.00	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06			A *
7* (670)	F2	2.00	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06			A *
7* (680)	F2	6.75	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06			A *
7* (690)	F2	3.75	CMM	QA		00064	SEE IGES	339-E.RO 07-27-06			A *
7* (700)	F1	4X Ø.75-10 UNC ▽ 1.50	THREAD PLUG GAGE	QA		A-681	THREAD AND DEPTH A CEPT	495-D.CO 07-26-06			A *
7* (710)	D1	2X 1.56 OPEN THRU	CALIPER	QA		J-707	1.56 / 1.56	339-E.RO 07-27-06			A *
7* (720)	C1	.375-16 UNC-2B TAP ▽ .75 .03 X 45° CHAMFER 6X	THREAD PLUG GAGE	QA		A-444	ACCEPT	339-E.RO 07-27-06			A *
7* (730)	C4	VERIFY THAT HOLE LOCATIONS ARE SCRIBED ON THE PART.		QA		VISUAL	ACCEPT	533-B.CL 07-26-06			A *
7* (740)	B3	8.50 DISTANCE BETWEEN SCRIBE MARKINGS.	CALIPER	QA		J-1389	8.51	495-D.CO 07-26-06			A *
9* (750)	H1	2X Ø.50	PIN GAGE	QA		J-651-2	.500	533-B.CL 07-26-06			A *
9*	B7	TC2	DEPTH MICROMETE	QA		J-1024	.628 DIA. DEPTH 2. 639 AND 3.640	533-B.CL			A

* To Far Right Indicates Data Package Requirement

NOTE: the recording of false, fictitious, or fraudulent statements or entries on this document may be punished as a felony under federal statutes including federal law, title 18, chapter 47.

INSPECTION DATA CHECKLIST

(760)		HOLE TO BE .625" IN DIAMETER APPROX. 2.52" DEEP AND .25" IN DIAMETER AT LEAST 1" DEEP.	CALIPER			J-707		07-26-06		*
*		TC1 LOCATION AND CONFIGURATION MODIFIED. HOLE TO HAVE .625 CLEARANCE AND AT LEAST 1" OF DEPTH AT THE .25" DIA	DEPTH MICROMETE	QA		J-1024	.625 DIA. DEPTH 1.060	533-B.CL		A
(770)			CALIPER			J-707		07-26-06		*
10* (780)	F5	 .5 A B C INNER AS CAST SURFACES	CMM	QA		00064	-.444 TO .053 [N/C: 20201-Doc:NC20201]	339-E.RO 07-27-06		R *
10* (790)	D5	 -.12 -.25 A B C WING SURFACES	CMM	QA		00064	-.122 TO -.209	339-E.RO 07-27-06		A *
Drawing ID: NCSX-CSPEC-141-03 Rev: 11			INSPECTION INSTRUCTIONS			RESULTS		INSPECTED BY		
SHEET	ZONE	CHARACTERISTIC	GAGE/EQUIP	BY	SAMPLE	SER#	DATA/REMARKS	INSP	VERFD	AUDIT
4* (800)	3.1.1.4	¹²⁵ THE TWO "L" MACHINED SURFACES OF TEE MUST HAVE A RMS OF 125.	PROFILOMETER	QA		J-1109	8 TO 30	533-B.CL 07-26-06		A *

Employees: 242-M.Griffith / 339-E.Root / 495-D.Coffman / 533-B.Clevenger

* To Far Right Indicates Data Package Requirement

NOTE: the recording of false, fictitious, or fraudulent statements or entries on this document may be punished as a felony under federal statutes including federal law, title 18, chapter 47.