

ITEM INSPECTED		
APPEARANCE	Surface condition (scratches, stains); Assembly (looseness, misalignment, gaps); Printing	
FUNCTIONS	Display	Liquid crystal display
	Controls	Power switch, Panel switch
	Input/Output	SCSI Connector
PERFORMANCE	Accuracy <Conditions> Distance: 600 mm / 1000 mm Environment Temperature: 20 °C Relative Humidity: 65 % or less Object: Our standard block Calculation: By our software	TELE: X, Y, Z: $\pm 0.05$ mm / $\pm 0.10$ mm MIDDLE: X, Y, Z: $\pm 0.10$ mm / $\pm 0.20$ mm WIDE: X, Y, Z: $\pm 0.20$ mm / $\pm 0.40$ mm
	Precision(Z, $\sigma$ ) <Conditions> Distance: 600 mm / 1000 mm Environment Temperature: 20 °C Relative Humidity: 65 % or less Object: Our standard plate Calculation: By our software	TELE: 0.008 mm / 0.024 mm MIDDLE: 0.016 mm / 0.048 mm WIDE: 0.032 mm / 0.096 mm
	Others	Flatness, Color reproducibility, Resolution (color data)

検査項目		
外観	傷・汚れ・隙間・段差・がた・表面処理・印刷	
機能	表示	液晶表示
	キースイッチ	電源スイッチ・パネルスイッチ
	入出力	SCSIコネクタ
性能	精度 <測定条件> 距離: 600 mm / 1000 mm 環境 温度 : 20 °C 相対湿度: 65 %以下 対象: 当社標準立体 処理: 当社ソフトウェア	TELE: X, Y, Z: $\pm 0.05$ mm / $\pm 0.10$ mm MIDDLE: X, Y, Z: $\pm 0.10$ mm / $\pm 0.20$ mm WIDE: X, Y, Z: $\pm 0.20$ mm / $\pm 0.40$ mm
	精度 (Z, $\sigma$ ) <測定条件> 距離: 600 mm / 1000 mm 環境 温度 : 20 °C 相対湿度: 65 %以下 対象: 当社標準平面板 処理: 当社ソフトウェア	TELE: 0.008 mm / 0.024 mm MIDDLE: 0.016 mm / 0.048 mm WIDE: 0.032 mm / 0.096 mm
	その他	平面性・色再現性・解像度 (カラーデータ)