



NOTES:

1. INTERPRET DIMENSIONS AND TOLERANCES PER ANSI Y14.5M
2. DIMENSIONS ARE IN INCHES
3. DIMENSIONS APPLY AT TEMPERATURE OF 20-30°C (68-86°F)
4. DRAWING DEPICTS FINAL MACHINED STATE OF PART DEFINED BY  
PRO/ENGINEER FILE SE124-014.PRT
5. APPROXIMATE WEIGHT= 0.37 lbs.
6. MINIMUM RADIAL ULTIMATE STATIC LOAD REQUIREMENT 20,000 LBS
7. ALL METAL, THREE PIECE ASSEMBLY.
8. MAXIMUM OPERATING TEMPERATURE 662°F.
9. MISALIGNMENT ANGLE SHALL BE A MINIMUM OF  $\pm 6$  DEGREES



SCALE: 2.00

next assy	AR	AR		- I	VERTICAL SUPPORT ROD END, FEMALE	TITANIUM 6AL-4V		I
	SE124-051	SE124-054	CAGE CODE	PART OR IDENTIFYING NO	NOMENCLATURE OR DESCRIPTION	MATERIAL	SPECIFICATION	FIND NO
				NEXT ASSEMBLY	PARTS LIST			

[illegible]

NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, IS MADE AS TO THE ACCURACY, COMPLETENESS OR USEFULNESS OF THE INFORMATION OR STATEMENTS CONTAINED IN THESE DRAWINGS, OR THE INFORMATION OR DISCLOSURE OF ANY INFORMATION, APPARATUS, METHOD OR PROCESS DISCLOSED IN THESE DRAWINGS MAY NOT INFRINGE PRIVATE RIGHTS OF OTHERS. NO LIABILITY IS ASSUMED WITH RESPECT TO THE USE OF, OR FOR DAMAGES RESULTING FROM THE USE OF, ANY INFORMATION, APPARATUS, METHOD OR PROCESS DISCLOSED IN THESE DRAWINGS. DRAWINGS MADE AVAILABLE FOR INFORMATION TO BIDDER ARE NOT TO BE USED FOR OTHER PURPOSES, AND ARE TO BE RETURNED UPON REQUEST OF THE FORWARDING CONTRACTOR.

THIS DRAWING PRODUCED  
ON PRO-ENGINEER