

Type	Conductor Size	Tolerance	Ga.	Dia.	CMA	Bunch #1	Bunch #2	Bunch #3	Cable
	w/o 0.004 in. serve			(in.)					
1	0.500 in. x 0.625 in.	+/- 0.010 in.	36	0.005	300,000	(68) @ 1.5 in. RHL	(3) @ 3 in. RHL	(5) @ 3 in. RHL	(12) @ 6 in. LHL
2a	0.250 in. x 0.3125 in.	+/- 0.010 in.	32	0.008	290,000	(25) @ 1.5 in. RHL	(7) @ 3 in. RHL		(7) @ 6 in. LHL
2b	0.250 in. x 0.3125 in.	+/- 0.010 in.	32	0.008	290,000	(25) @ 2.0 in. LHL	(7) @ 4 in. LHL		(7) @ 4 in. RHL
3	0.539 in. x 0.660 in.	+/- 0.010 in.	34	0.006	336,729	(101) at 3 in. RH	(7) @ 5.5 in. RHL		(12) @ 6 in. LHL
4	0.539 in. x 0.660 in.	+/- 0.010 in.	34	0.006	336,729	(101) at 3 in. RH (101) at 3 in. LHL	(7) @ 5.5 in. RHL (7) @ 5.5 in. LHL		(9) @ 6 in. LHL (3) @ 6 in. RHL
5	0.539 in. x 0.660 in.	+/- 0.010 in.	34	0.006		(101) at 3 in. RH (101) at 3 in. RH	(7) @ 5.5 in. RHL (7) @ 5.5 in. RHL		(9) @ 6 in. LHL (3) straight center
6	0.310 in. x 0.351 in.	+/- 0.010 in.	34	0.006		(44) @ 2.5 in. RHL (44) @ 2.5 in. LHL	(5) @ 3 in. RHL (5) @ 3 in. LHL		(9) @ 3.5 in. LHL (3) @ 3.5 in. RHL
7	0.342 in. x 0.383 in.	+/- 0.008 in.	34	0.006		(54) @ 2.5 in. RHL (54) @ 2.5 in. LHL	(5) @ 3.5 in. RHL (5) @ 3.5 in. LHL		(9) @ 5.5 in. LHL (3) @ 5.5 in. RHL