

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

NSCX PROTOTYPE VACUUM VESSEL SEGMENT

Sub ID 0	Part ID NSCX PROTOTYPE VACUUM VESSEL SEGMENT	Qty 1	Drawing ID / Rev SE121 / A
--------------------	--	-----------------	--------------------------------------

Operation Sub: 0 / Seq: 10 (F)	Resource 700-BLUE TEAM, ENGINEERING SOW 3.2.1 TASK 2 MIT/QA PLANS FOR PVVS FOR VVSA	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121 / A
---	---	-----------------------	-------------------------	----------------------	--------------------------------------

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Piece # 10 (F)	Part ID INCONEL625_062_GTAW-WELD WIRE/GTAW, .062 DIA Vendor Part ID: INCONEL625_062_GTAW Mfg Part ID: INCONEL 625 Material Certification: TRACE ID: 38561 Part Number: SE121-001P	Qty 10.0	Drawing ID / Rev	Vendor 4434	Dimensions
---------------------------------	---	--------------------	-------------------------	-----------------------	-------------------

Piece # 30 (F)	Part ID INCONEL625_093_GTAW-WELD WIRE/GTAW, .093 DIA Vendor Part ID: INCONEL625_093_GTAW Mfg Part ID: INCONEL 625 Material Certification: Part Number: SE121-001P	Qty 15.0	Drawing ID / Rev	Vendor 4434	Dimensions
---------------------------------	---	--------------------	-------------------------	-----------------------	-------------------

Operation Sub: 0 / Seq: 11 (F)	Resource 700-BLUE TEAM, ENGINEERING SOW 3.1 TASK 1 3.1.1 METHODS FOR FABRICATING VVSA 3.1.2 DESIGN CHANGES 3.1.3 PRELIMINARY MIT/AQ FOR VVSA 3.1.4 BUDGETARY COST/SCHEDULE FOR VVSA	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev
---	--	-----------------------	-------------------------	----------------------	-------------------------

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation Sub: 0 / Seq: 12 (F)	Resource 700-BLUE TEAM, ENGINEERING SOW 3.3.1 & SOW 3.3.2 Task 8	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev
---	---	-----------------------	-------------------------	----------------------	-------------------------

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

3.3.1 FINAL MIT/QA FOR VVSA
 3.3.2 FINAL COST/SCHEDULE FOR VVSA

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 0 / Seq: 13 (F)	700-BLUE TEAM, ENGINEERING ENGINEERING, PLANNING & PROJECT MGT TASK 9	1.00	1.00	1.00	

FOLLOWING IS A LIST STANDARD OPERATING PROCEDURES AND WORK INSTRUCTIONS THAT APPLY IN PART OR IN WHOLE TO THE EXECUTION OF THIS WORK ORDER.

ENGINEERING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING STANDARD OPERATING PROCEDURES: ENGSOP01 - Mfg. Quality Plans; ENGSOP02 - Specification-Standard Control; ENGSOP03 - Internal Drawing Generation; ENGSOP04 - Drawing Control.

CAD / CAM OPERATIONS WILL BE PERFORMED PER THE FOLLOWING STANDARD OPERATING PROCEDURE: CADSOP01 - CNC Program Control;

MANUFACTURING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING STANDARD OPERATING PROCEDURES: MFGSOP01 - Project Manufacturing; MFGSOP02 - Material Handling and Storage; MTL SOP01 - Material Storage; PCSOP01 - Production Control; QASOP01 - Nonconformance Control; QASOP03 - Traceability-Identification

QUALITY ASSURANCE AND INSPECTION OPERATIONS WILL BE PERFORMED PER THE FOLLOWING STANDARD OPERATING PROCEDURES: QASOP01 - Nonconformance Control; QASOP05 - Calibration

RECEIVING INSPECTION OPERATIONS WILL BE PERFORMED PER THE FOLLOWING STANDARD OPERATING PROCEDURE: QASOP04 - Receiving Inspection

IN-PROCESS INSPECTION OPERATIONS WILL BE PERFORMED PER THE FOLLOWING STANDARD OPERATING PROCEDURE: QASOP02 - In Process Inspection

SHIPPING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING STANDARD OPERATING PROCEDURE: SHSOP01 - Shipping-Packaging

MACHINING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING STANDARD OPERATING PROCEDURE: TLGSOP01 - Cutting Tool Control

WELDING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING STANDARD OPERATING PROCEDURES: WLDSOP02 - Qualification of Welders and WPS; WLDSOP03 - Welding Process Development; WLDSOP04 - Stores Control of Weld Wire; WLDSOP05 - Weld Mapping; WLDSOP06 - Welding Filler Metal and Flux Procurement

ENGINEERING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTIONS: ENGWI001 - Material Card; ENGWI002 - Drawing Control; ENGWI003 - Bill of Manufacturing; ENGWI005 - Engineering Contract Review; ENGWI007 - Work Order Review Release; ENGWI008 - Operation Cards; ENGWI009 - Quality Planning; ENGWI010 - Service Cards; ENGWI013 - Work Order Header Card Maintenance; ENGWI014 - Inspection Fields; ENGWI019 - Nonconformance to Customers.

CAD / CAM OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTIONS: CADWI004 - Developing a CAD/CAM program; CADWI005 - Updating CAD/CAM Program or File

MANUFACTURING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTIONS: MFGWI018 - Workmanship; PCWI001 - Use of MTM Routing; PCWI004 - Scheduling System Procedures

CLEANING / WASHING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTION: MFGWI005 - High Pressure-High Temperature Water Cleaning of Parts

SUBCONTRACT OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTION: PCWI005 - Subcontract Procedure; PURWI002 - Vendor Setup and Assessment

NON-DESTRUCTIVE TESTING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTIONS: NDTWI001 - NDT Exam Personnel Qualification; NDTWI011 - Visual Weld Inspection

QUALITY ASSURANCE, IN-PROCESS INSPECTION OPERATIONS AND/OR RECEIVING INSPECTION OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTIONS: QAWI001 - MTM Inspection Method Guidelines; QAWI006 - Sampling Inspection Criteria; QAWI008 - Receiving Ordered Material; QAWI010 - Calibration; QAWI015 - Checking Out and Returning Gauges; QAWI017 - Recording Inspection Results; QAWI018 - Quality Sign Off Control; QAWI020 - Organization and Control of Quality Records; QAWI021 - Quality Record Storage and Retention; QAWI023 - Nonconformance System Navigation; QAWI026 - Part Relocation with SMX; QAWI027 - SMX Part Inspection Checklist; QAWI028 - QAP Data Package Generation; QAWI029 - Scanning Certifications; QAWI031 - Material Certification Program.

SHIPPING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTIONS: SHWI002 - Guidelines for Shipping Documentation; SHWI003 - General

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Guidelines for Building Containers; SHWI004 - Guidelines for Loading Parts for Shipment; SHWI005 - General Guidelines for Packaging Parts; SHWI007 - Guidelines for Coordinating Transport.

WELDING OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTIONS: WLDWI003 - Welding Personnel Training; WLDWI004 - Welder Performance Qualification; WLDWI005 - Storage and Maintenance of Welding Documents; WLDWI006 - Welding Engineering Work Order Review Process; WLDWI007 - Weld Wire and Stub Control; WLDWI008 - Assessment of Welder's Ability

BLAST BOOTH OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTIONS: SBWI001 - General Sandblast Guidelines;

MATERIAL PROCUREMENT OPERATIONS WILL BE PERFORMED PER THE FOLLOWING WORK INSTRUCTIONS: PURWI001 - Purchasing Data; PURWI002 - Vendor Setup and Assessment

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 0 / Seq: 20 (F)	825-FINAL INSPECTION - PLANTS 1	1.00	1.00	1.00	SE121 / A
	FINAL VISUAL INSPECTION (ENGINEERING CONCURRENCE REQUIRED). FINAL CLEANLINESS VERIFICATION PER PP475 AND PREPARE CERTIFICATION COMPILE ELECTRONIC DATA BOOK INFORMATION PER MTM QAP. TAKE SEVERAL PHOTOGRAPHS OF PART PREPARE C OF C AND REQUEST FOR SHIPPING RELEASE (CONTACT ENGINEERING (DOUG MCCORKLE) FOR RELEASE FORM IF NOT AVAILABLE ELECTRONICALLY. Test Certification: CLEANLINESS REPORT Rev: Part Number: SE121-003P Part Description: PVVS Specification: PP475 Rev: --				

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 4 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 0 / Seq: 30 (F)	425-SHIPPING - PLANTS 1 & 2	1.00	1.00	1.00	SE121 / A
	SHIP PER CUSTOMER RELEASE FORM (CONTAINER MANUFACTURED IN SUB I.D. 28) AT A MINIMUM ENSURE THE PART IS COMPLETELY WRAPPED WITH PLASTIC FOAM AND SHRINK WRAP. SPECIAL CRATE REQUIREMENTS: CONTAINER MUST BE CLEARLY MARKED WITH THE FOLLOWING INFORMATION: SUPPLIER: MAJOR TOOL & MACHINE, INC. 1458 E. 19TH ST. INDIANAPOLIS, IN 46218 CONTENTS: SE121 NCSX PVVS				

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 0 / Seq: 9999	600-DO NOT USE - PC AUTO PROJE	1.00	1.00	1.00		TESTNG/MISC
	Drw N/A IDC N/A	IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 0	NDT Count: 0 WPS Count: 0

Sub ID	Part ID	Qty	Drawing ID / Rev
---------------	----------------	------------	-------------------------

Workorder	Part ID	Qty	Drawing ID / Rev	Engineer
64880/1		1	SE121 / A	BLUE/DOUG MCCORKLE
1	SE121 PROTOTYPE VACUUM VESSEL	1	SE121 / A Parent Sub:0 Op:20	

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 10 (F)	230-FABRICATION - WEIDNER FABRICATION OPERATION # 1	1.00	1.00	1.00	SE121-001P / A

INSTALL THE FOLLOWING DIE FORMED PANELS ONTO FABRICATION FIXTURE:

- SE121-001P-2 PANEL 1
- SE121-001P-2 PANEL 2
- SE121-001P-2 PANEL 3
- SE121-001P-2 PANEL 4
- SE121-001P-2 PANEL 5

START BY SETTING THE DATUM -B- SURFACE (10 DEGREE OFFSET) ONTO THE MACHINED REGISTER OF THE BUILD FIXTURE BASE-PLATE. TRIM, FIT, AND ALIGN EACH PANEL TO IT'S RESPECTIVE ADJACENT PANEL AND FIXTURE REST STOPS. NOTE THAT THE FIXTURE REST STOPS ARE POSITIONED AT NOMINAL (+.090") GEOMETRIC POSITION TO AVOID STARTING ANY LOWER THAN MID-TOLERANCE. GAPS BETWEEN THE PRODUCTION PANELS AND FIXTURE REST STOPS (UP TO .090") ARE PERMITTED.

THE TOP EDGE OF EACH PANEL SHOULD REST APPROXIMATELY .04" ABOVE THE FIXTURE RISER FACE.

ENSURE THE MATERIAL THICKNESS IS ADEQUATE TO ALLOW TYPICAL REDUCTION RESULTING FROM GRINDING / BLENDED / POLISHING THE WELDS.

INSPECT THICKNESS WITH A U-T GAGE. NOTIFY ENGINEERING (DOUG McCORKLE) IF CONCERNS EXIST.

ENSURE EACH PANEL IS ALIGNED (SMOOTH AND CONTINUOUS) TO ITS ADJACENT MEMBER AND MIS-MATCH IS MINIMIZED. CWI / ENGINEERING CONCURRENCE REQUIRED.

GRIND PREPS ON EACH PANEL WELD JOINT (60 DEGREE INCLUDED). THE WELD JOINT ROOT MUST BE ORIENTATED TO THE INSIDE OF THE VESSEL (VACUUM SIDE). NOTE BURNTHROUGH, AND BACKWELD FACES SHOULD BE KEPT AS NARROW AS POSSIBLE.

PURGE EACH WELD JOINT WITH 100% ARGON. PURGE DAM MATERIAL MUST BE MADE FROM EITHER 625 INCONEL OR 300 SERIES STAINLESS STEEL.

TACK WELD ALL FIVE PANELS TOGETHER.

ASSIST Q/A WITH PROFILE VERIFICATION.

Part Number: SE121-001P

Part Description: NCSX PVVS

IDC Count : 2 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 1

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 20 (F)	805-INPROCESS INSPECTION - PLA INSPECTION OPERATION # 1	1.00	1.00	1.00	SE121-001P / A

AFTER PART IS COMPLETELY TACK WELDED, INSPECT / VERIFY POSITIONING, FITUP, AND PROFILE OF TACK WELDED PER THE FOLLOWING:

ENSURE THE PART PROFILE IS WITHIN THE UPPER HALF OF THE APPLIED BI-LATERAL TOLERANCE AS FOLLOWS: VERIFY THAT NO INSPECTION POINT IS ABOVE THE HIGH LIMIT OF TOLERANCE (OUTWARD) OR BELOW NOMINAL (INWARD).

RECORD ACTUAL (HIGH/LOW RANGE) ON MTM IDC

REPORT ANY OUT OF TOLERANCE READINGS VIA MTM NCR

NOTIFY ENGINEERING (DOUG McCORKLE) FOR EVALUATION OF RESULTS PRIOR TO RELEASING THE PART BACK TO PRODUCTION.

INSPECTION POINT GRID: 6" CENTERS THROUGHOUT WITH 1" CENTERS AT AND NEAR WELD JOINTS.

ENSURE THE FIXTURE DATUM TARGETS ARE ADEQUATELY POSITIONED FOR THE NEXT SEQUENTIAL INSPECTION

INSPECT AND RECORD THE MAGNETIC PERMEABILITY OF THE WELD ZONES.

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Part Number: SE121-001P
Part Description: NCSX PVVS

IDC Count : 2 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 30 (F)	230-FABRICATION - WEIDNER FABRICATION OPERATION # 2	1.00	1.00	1.00	SE121-001P / A

INSTALL STIFFENER (FIXTURING) TO THE TOP OF THE VESSEL. TACK WELD THE STIFFENER TO THE PART.
NOTE THAT THE STIFFENER MATERIAL IS ALSO INCO 625, NO TABS REQUIRED.

BACK PURGE THE WELD JOINT SURFACES WITH 100% ARGON. PURGE DAM MATERIAL MUST BE MADE FROM EITHER 625 INCONEL OR 300 SERIES STAINLESS STEEL.

WELD ROOT PASSES (INCREMENTALLY, USING BACK-STEPPING METHOD TO MINIMIZE SHRINKAGE) ON ALL FIVE WELD JOINTS.

NOTE THAT THE BACK SIDE OF THE JOINT MUST REMAIN PURGED UNTIL THE ENTIRE JOINT IS COMPLETELY FILLED.

NOTE BURNTHROUGH, AND BACKWELD FACES SHOULD BE KEPT AS NARROW AS POSSIBLE.

CWI VISUAL INSPECT ROOT WELDS 100% UNDER 8X MAGNIFICATION PER ASME CODE ARTICLE 6, SECTION V. ACCEPTANCE PER AWS D1.6, 6.29.1.

Test Certification: CWI CERTIFICATE Rev:

Part Number: SE121-001P
Part Description: NCSX PVVS

IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 3 NDT Count: 0 WPS Count: 1

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 40 (F)	805-INPROCESS INSPECTION - PLA INSPECTION OPERATION # 2	1.00	1.00	1.00	SE121-001P / A

AFTER THE ROOT WELDS ARE COMPLETE (FABRICATION DEPT. WILL COORDINATE); RE-INSPECT / VERIFY PART PROFILE IS WITHIN APPLIED TOLERANCE AND RECORD WELDING SHRINKAGE / DISTORTION REALIZED TO THIS POINT.

INSPECTION POINT GRID: 6" CENTERS THROUGHOUT WITH 1" CENTERS AT AND NEAR WELD JOINTS.

RECORD ACTUAL (INDIVIDUAL) MEASUREMENTS ON INSPECTION FORM (SE121-2MTM). RECORD ACTUAL (HIGH/LOW RANGE) ON MTM I.D.C.

INSPECT AND RECORD MAGNETIC PERMEABILITY.

REPORT ANY OUT OF TOLERANCE READINGS VIA MTM NCR.

NOTIFY ENGINEERING (DOUG McCORKLE) FOR EVALUATION OF RESULTS PRIOR TO RELEASING PART. NOTE THAT PROFILE READINGS SHOULD REMAIN NEAR TO ABOVE NOMINAL. INWARD DISTORTION APPROACHING THE LOW LIMIT OF TOLERANCE MUST BE ADDRESSED (AND CORRECTIVE ACTION IMPLEMENTED) PRIOR TO COMPLETING WELDING PROCESS.

ENSURE THE FIXTURE DATUM TARGETS ARE ADEQUATELY POSITIONED FOR THE NEXT SEQUENTIAL INSPECTION.

Part Number: SE121-001P
Part Description: NCSX PVVS

IDC Count : 2 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 70 (F)	230-FABRICATION - WEIDNER FABRICATION OPERATION # 3	1.00	1.00	1.00	SE121-001P / A

Workorder
64880/1

Part ID

Qty Drawing ID / Rev
1 SE121 / A

Engineer
BLUE/DOUG MCCORKLE

AFTER OBTAINING ENGINEERING, Q/A PROFILE ACCEPTANCE, AND AUTHORIZATION TO PROCEED, WELD THE REMAINDER OF THE STRUCTURAL WELD JOINTS. SEQUENCE WELDING AND UTILIZE BACKSTEPPING METHODS TO MINIMIZE DISTORTION AND NUMBER OF INTER-PASSES. CWI VISUAL INSPECT EACH WELD PASS 100% UNDER 8X MAGNIFICATION PER ASME CODE ARTICLE 6, SECTION V. ACCEPTANCE PER AWS D1.6, 6.29.1. AFTER WELDING IS COMPLETE, REMOVE ANY STIFFENING / SUPPORT DEVICES. BLEND / TOUCH UP ATTACHMENT WELDS AS REQUIRED. LAYOUT THE PORT ASSEMBLY LOCATION. (ANGULAR LOCATION / OVERALL LENGTH AND OUTLINE ARE SCRIBED ON FIXTURE). UTILIZE THE LASER TRACKER TO ENSURE POSITION. WELD THE PORT EXTENSION SUB-ASSEMBLY IN PLACE PER DRAWING. BACK PURGE THE WELD JOINT SURFACES WITH 100% ARGON. PURGE DAM MATERIAL MUST BE MADE FROM EITHER 625 INCONEL OR 300 SERIES STAINLESS STEEL. NOTE THAT THE BACK SIDE OF THE JOINT MUST REMAIN PURGED UNTIL THE ENTIRE JOINT IS COMPLETELY FILLED. CWI VISUAL INSPECT THE PORT EXTENSION WELD 100% UNDER 8X MAGNIFICATION PER ASME CODE ARTICLE 6, SECTION V. ACCEPTANCE PER AWS D1.6, 6.29.1. FINISH POLISHING (RESTORE TO A 32 MICRO-INCH SURFACE FINISH) AND CLEANING THE INTERIOR SURFACES OF THE PORT SUB-ASSEMBLY. REFER TO CLEANING PROCEDURE PP475 CWI NOTE: THE VISUAL INSPECTION CERTIFICATE SHOULD SPECIFY EACH WELD JOINT / STRINGER PASS. IT SHOULD ALSO CLEARLY DIFFERENTIATE BETWEEN THE STRUCTURAL WELDS AND THE PORT EXTENSION WELDS.

Test Certification: CWI CERTIFICATE Rev:
Part Number: SE121-001P
Part Description: NCSX PVVS
Specification: ASNT 2055 SNT-TC-1A Rev: 1996

Drw N/A IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 4 NDT Count: 0 WPS Count: 1

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	IDC Count	Dwg Count	Pgm Count	QAP Count	NDT Count	WPS Count
Sub: 1 / Seq: 71 (F)	265-PAINT BOOTH BAKE OUT AT 150 DEGREES C (302F) FOR 6 HOURS TO REMOVE MOISTURE IN PREPARATION FOR THE FOLLOWING SEQUENTIAL OPERATION (VACUUM / LEAK TESTING). NOTE THAT THIS SEQUENCE MUST BE COORDINATED WITH THE VACUUM TESTING. CONTACT ENGINEERING (DOUG MCCORKLE) AND SUBCONTRACT ADMINISTRATOR (BOB JOACHIM) PRIOR TO BEGINNING FOR TIMING AND COORDINATION. CYCLE START TIME WILL BE ADVISED. Part Number: SE121-001P Part Description: NCSX PVVS Furnace charts: FURNACE CHART	1.00	1.00	1.00	SE121 / A	0	0	0	4	0	1

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	IDC Count	Dwg Count	Pgm Count	QAP Count	NDT Count	WPS Count
Sub: 1 / Seq: 72 (U)	230-FABRICATION - WEIDNER SETUP AND PREPARE FOR SUBCONTRACT VACUUM TESTING (WHICH WILL BE PERFORMED AT SEQUENCE 73) AND RADIOGRAPHIC INSPECTION (WHICH WILL BE PERFORMED AT SEQUENCE 75) AS FOLLOWS: INSTALL THE SEAL AND VACUUM TEST CAP TO THE CONFLAT FLANGE INSTALL AND TORQUE THE FLANGE INSTALLATION BOLTS PER MANUFACTURERS INSTRUCTIONS. LAYOUT ALL STRUCTURAL WELDS FOR 100% X-RAY. ASSIST WITH THE VACUUM TEST AND ENSURE THE FOLLOWING PRECAUTIONS ARE OBSERVED:	1.00	1.00	1.00		0	0	0	3	0	0

Caution: The vacuum test procedure will subject the vessel to an internal vacuum that generates tremendous forces. Failure of any part of the vessel or test equipment could result in implosive/explosive reactions, ejected parts

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

and dangerous noise levels. Unnecessary personnel should vacate the test area whenever a vacuum is present in the vessel (Except essential personnel).

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 1 / Seq: 73 (F)	450-SUBLET VACUUM TEST THE PORT EXTENSION SUB-ASSEMBLY (WELDED TO THE VESSEL WALL) PER THE FOLLOWING: PP476 (PPPL NCSX PVVS VVSA VACUUM TESTING PROCESS PARAMETERS) THE PORT UNDER TEST SHALL BE EVACUATED USING A TURBOMOLECULAR PUMP TO AN INTERNAL PRESSURE OF LESS THAN OR EQUAL TO 1 X 10 ⁽⁻⁷⁾ TORR. THE TOTAL HELIUM LEAK RATE FOR THE PORT EXTENSION SHALL BE LESS THAN OR EQUAL TO 1.7 X 10 ⁽⁻⁹⁾ TORR-L/S. MTM CONTRACT ADMINISTRATOR NOTE: THIS SEQUENCE MUST BE COORDINATED WITH THE PRECEDING (BAKE OUT) OPERATION. PRODUCTION CONTROL WILL INIATE COORDINATION PRIOR TO BEGINNING THE BAKE OUT OPERATION. Part Number: SE121-001P Part Description: NCSX PVVS Customer: PPPL Test Certification: VACUUM TEST CERTIFICATE Rev: Specification: ASTM E 498 Rev: 95	1.00	1.00	1.00	SE121-003P / --	MISC/SUBLET

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 5 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 1 / Seq: 75 (F)	818-MQS CONTRACTOR X-RAY 100% RADIOGRAPHIC INSPECT THE 5 STRUCTURAL WELDS (LOCATIONS IDENTIFIED ON PART) PER THE FOLLOWING: ASME SECTION VIII, DIVISION 1, UW-51 Specification: ASME SECTION VIII Map(s): RADIOGRAPHIC INSPECTION MAP Rev: Part Number: SE121-001P Part Description: NCSX PVVS Material Type: 625 INCONEL Test Certification: RADIOGRAPHIC CERTIFICATE Rev: Material Thickness: .375"	1.00	1.00	1.00	SE121-001P /	

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 7 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 1 / Seq: 80 (F)	805-INPROCESS INSPECTION - PLA INSPECTION OPERATION # 3 RE-INSPECT / VERIFY PART PROFILE IS WITHIN APPLIED TOLERANCE AND RECORD PRIMARY STRUCTURAL WELDING SHRINKAGE / DISTORTION. INSPECTION POINT GRID: 6" CENTERS THROUGHOUT WITH 1" CENTERS AT AND NEAR WELD JOINTS. RECORD ACTUAL (INDIVIDUAL) MEASUREMENTS ON INSPECTION FORM (SE121-2MTM). RECORD ACTUAL (HIGH/LOW RANGE) ON MTM IDC INSPECT AND RECORD MAGNETIC PERMEABILITY. REPORT ANY OUT OF TOLERANCE READINGS VIA MTM NCR. NOTIFY ENGINEERING (DOUG McCORKLE) FOR EVALUATION OF RESULTS PRIOR TO RELEASING PART. ENSURE THE FIXTURE DATUM TARGETS ARE ADEQUATELY POSITIONED FOR THE NEXT SEQUENTIAL INSPECTION.	1.00	1.00	1.00	SE121-001P / A	

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Part Number: SE121-001P
Part Description: NCSX PVVS

IDC Count : 2 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 90 (F)	230-FABRICATION - WEIDNER	1.00	1.00	1.00	SE121-002P / --
	LAYOUT AND PLASMA CUT THE PORT EXTENSION TUBE OFF THE VESSEL WALL (NORMAL TO VESSEL SURFACE) PER DRAWING. PLASMA CUT THE PORT OPENING INTO THE VESSEL WALL PER DRAWING (CUT UNDERSIZE ALLOWING FOR GRINDING / SIZING TO PORT EXTENSION I.D.) USE A CIRCLE CUTTING DEVICE TO ENSURE PROPER SIZE AND ROUNDNESS. REMOVE RECAST / HEAT AFFECTED ZONE FROM EACH CUT SURFACE BY GRINDING. GRIND / BLEND THE PORT EXTENSION EDGE AND VESSEL WALL OPENING SMOOTH (MAINTAINING PROPER SIZE AND RELATIONSHIP TO THE I.D. OF THE PORT EXTENSION TUBE). PREP THE EDGES OF THE PORT STUB AND PORT EXTENSION TUBE FOR RE-INSTALLATION. POSITION AND SKIP WELD THE BACKING RING (SE121-003P-4) IN PLACE (TO THE END OF THE DETACHED PORT EXTENSION TUBE) PER DRAWING SE121-003P RE-INSTALL THE PORT EXTENSION ASSEMBLY TO THE PORT STUB AND WELD IN PLACE PER DRAWING SE121-003P. GRIND AND BLEND THE PORT EXTENSION INTERIOR WELD SMOOTH. CWI VISUAL INSPECT EACH WELD PASS 100% UNDER 8X MAGNIFICATION PER ASME CODE ARTICLE 6, SECTION V. ACCEPTANCE PER AWS D1.6, 6.29.1. ENSURE ALL COSMETIC WELDING AND BLENDING IS COMPETE, ENSURE ALL INTERIOR SURFACES ARE POLISHED AND CLEANED, AND PREPARE PART FOR FINAL (EXTERIOR) BLAST AND FINAL INSPECTION.				

Test Certification: VISUAL INSPECTION CERT Rev:
Part Number: SE121-003P
Part Description: PVVS
Specification: ASNT 2055 SNT-TC-1A Rev: 1996

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 4 NDT Count: 0 WPS Count: 1

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 100 (F)	805-INPROCESS INSPECTION - PLA	1.00	1.00	1.00	SE121 / A
	INSPECT PROFILE IN THE AREA OF THE PORT STUB / PORT EXTENSION. INSPECT MAGNETIC PERMEABILITY IN THE AREA OF THE PORT STUB / PORT EXTENSION WELDING. INSPECT THE INTERIOR SURFACE FINISH OF THE PORT EXTENSION. RECORD IDC DATA Part Number: SE121-003P Part Description: NCSX PVVS				

IDC Count : 3 Dwg Count: 0 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 110 (F)	260-SANDBLAST	1.00	1.00	1.00	SE121 / A
	MASK THE INTERIOR SURFACES AND FLANGE FACE. BLAST THE OUTSIDE SURFACE 100% USING 220 GRIT VIRGIN ALUMINUM OXIDE.				

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 115 (F)	230-FABRICATION - WEIDNER	1.00	1.00	1.00	SE121 / A
	REMOVE MASKING AND PROTECTIVE PLASTIC				

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

DETERGENT WASH / CLEAN PART PER PP475.

IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 1 / Seq: 120 (F)	805-INPROCESS INSPECTION - PLA FINAL PROFILE INSPECTION. INSPECT AND RECORD THE VESSEL PROFILE AND PORT EXTENSION POSITION. FINAL MAGNETIC PERMEABILITY VERIFICATION. VERIFY MAGNETIC PERMEABILITY OF THE STRUCTURAL WELDS, VESSEL WALL, PORT EXTENSION TUBE, CONFLAT FLANGE, FLANGE TO TUBE WELD. FINAL INTERIOR SURFACE FINISH VERIFICATION. VISUAL INSPECT THE ENTIRE INTERIOR, SAMPLE INSPECT (APROXIMATE 6" GRID) WITH PROFILOMETER. REFERENCE NDT-WI-??? (BEING DEVELOPED) RECORD IDC DATA Part Number: SE121-003P Part Description: NCSX PVVS Specification: ASME B46.1 Rev: 1995 Certification: MAG. PERMEABILITY REPORT Certification: PROFILE VERIFICATION REPORT Certification: INT. SURF. FINISH REPORT	1.00	1.00	1.00	SE121 / A

IDC Count : 5 Dwg Count: 0 Pgm Count: 0 QAP Count: 6 NDT Count: 0 WPS Count: 0

Sub ID 14	Part ID SE121-001P-2 PANEL # 1	Qty 1	Drawing ID / Rev I/ Parent Sub:1 Op:10
---------------------	--	-----------------	---

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 14 / Seq: 10 (F)	410-BURNOUT TABLE 1. PRIOR TO BEGINNING WORK, CONTACT Q/A TO PERFORM A SERIES OF MATERIAL THICKNESS AND MAGNETIC PERMEABILITY TESTS ON THE RAW MATEIRAL (PRIOR TO MATERIAL PROCESSING AND HANDLING BY MTM). 2. NEST AND PROGRAM PER PROVIDED GEOMETRY. 3. BURNOUT AND CLEANUP PANEL PER NESTING / PROGRAM. 4. CLEANUP EDGES / RADIUS CORNERS (.03" MIN. RAD). ENSURE ALL DROSS AND RE-CAST LAYER IS REMOVED. ENSURE THE CUT SURFACE IS BLENDED SMOOTH. 5. NOTIFY Q/A FOR VERIFICATION PRIOR TO MOVING TO THE NEXT WORK CENTER.	1.00	1.00	1.00	SE121-001P / A

Specification: ASTM A800 Rev: 91
Part Number: SE121-001P-2 PANEL 1
Part Description: DIE FORMED PANEL
Customer: PPPL
Specification: ASTM B443 Rev: 93

IDC Count : 1 Dwg Count: 1 Pgm Count: 0 QAP Count: 3 NDT Count: 0 WPS Count: 0

Piece #	Part ID	Qty	Drawing ID / Rev	Vendor	Dimensions
10 (F)	INCONEL 625_5-PLATE,NICKEL ALLOY .375" THK Vendor Part ID: INCONEL 625_5 INCONEL 625 (UNS N06625) PER ASTM B 443-00 ANNEALED MAGNETIC PERMEABILITY SHALL NOT EXCEED 1.00 (REF. ASTM A800). SURFACE MUST BE PROTECTED FROM CONTACT WITH IRON AND IRON ALLOY MATERIALS	4,198.1		1810	54.97*76.37

Workorder
64880/1

Part ID

Qty Drawing ID / Rev
1 SE121 / A

Engineer
BLUE/DOUG MCCORKLE

CERTS & MILL TEST REPORTS REQ'D WITH SHIPMENT.

Material Certification:

Part Number: SE121-001P-2 PANEL 1

Part Description: DIE FORMED PANEL

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev						
Sub: 14 / Seq: 15 (F)	805-INPROCESS INSPECTION - PLA INSPECT BLANK SIZE PER DRAWING VERIFY EDGES ARE SMOOTH AND CORNERS HAVE RADII APPLIED PER PREVIOUS SEQUENCE. INSPECT MATERIAL THICKNESS VISUAL INSPECT SURFACE FINISH INSPECT MAGNETIC PERMEABILITY RECORD IDC DATA Specification: ASTM A800 Rev: 91 Part Number: SE121-001P-2 PANEL 1 Part Description: DIE FORMED PANEL Customer: PPPL Specification: ASTM B443 Rev: 93 Specification: ASTM B46.1 Rev: 95	1.00	1.00	1.00	SE121-001P / A	IDC Count : 3	Dwg Count: 1	Pgm Count: 0	QAP Count: 6	NDT Count: 0	WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev						
Sub: 14 / Seq: 18 (F)	415-ROLLING/SHEAR/BRAKE PRESS ROLL PANEL BLANK INTO A CONE PER PROCESS DRAWING. ENSURE PLATE ROLLS ARE COMPLETELY CLEAN AND FREE OF DIRT, GRIME, FOREIGN MATTER, AND RAISED METAL PRIOR TO ROLLING. ENSURE THE PANEL BLANKS ARE PROTECTED WITH PLASTIC SHEET DURING THE ENTIRE PROCESS. NOTIFY ENGINEERING (DOUG McCORKLE) PRIOR TO PROCEEDING.	1.00	1.00	1.00	SE121-001P / A	IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 14 / Seq: 20 (F)	341-PACIFIC 750 LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PANEL BLANK (OR CONE) INTO THE DIE SET. HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE # _____. PANEL TO GAGE GAP TOLERANCE: .08" MAX. NOTIFY Q/A FOR PROFILE IDC VERIFICATION ENSURE THE PANEL MATERIAL EXTENDS BEYOND THE PERIMETER OF THE TRIM-LINES OF THE GAGE BY AT LEAST 1" (TO PROVIDE ADEQUATE STOCK ALLOWANCE FOR RE-POSITIONING, RE-STRIKING, AND ACCURATE TRIMMING). Part Number: SE121-001P-2 PANEL 1 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A				

Workorder	Part ID	Qty	Drawing ID / Rev	Engineer		
64880/1		1	SE121 / A	BLUE/DOUG MCCORKLE		
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0		
		QAP Count: 2	NDT Count: 0	WPS Count: 0		
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	
Sub: 14 / Seq: 25 (F)	260-SANDBLAST SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.	1.00	1.00	1.00	SE121-001P / A	
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	
		NDT Count: 0	WPS Count: 0			
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	
Sub: 14 / Seq: 27 (F)	230-FABRICATION - WEIDNER INSTALL AND WELD ANNEAL BRACING IN PLACE PER ENGINEERING SKETCH ENSURE PART IS CLEAN AND READY FOR SOLUTION ANNEAL CYCLE	1.00	1.00	1.00	SE121-001P / A	
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	
		NDT Count: 0	WPS Count: 1			
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 14 / Seq: 30 (F)	520-SUBLET, EXOTIC HEAT TREAT SOLUTION ANNEAL FORMED PANEL PER THE FOLLOWING: ATTACH A MINIMUM OF THREE EQUALLY SPACED THERMOCOUPLES TO THE FORMED PANEL CHARGE FURNACE AND HEAT PART UNTIL THERMOCOUPLE READINGS ARE WITHIN 1900 +/-15F. HOLD PART TEMPERATURE AT 1900 DEGREES F. (+/- 15 DEGREES) HOLD FOR 45 MINUTES (+/ 5 MINUTES) RAPID COOL (VIA. WATER QUENCHING OR FORCED AIR CIRCULATION) TO 1000 DEGREES F. OPEN AIR COOL TO AMBIENT TEMP. Specification: AMS2774 Rev: JUL95 Certification: H/T CERTIFICATE Part Number: SE121-001P-2 PANEL 1 Part Description: DIE FORMED PANEL Customer: PPPL Furnace charts: FURNACE CHART	1.00	1.00	1.00	SE121-001P / A	THRML TR/NA SA
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 6	NDT Count: 0
		WPS Count: 0				
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	
Sub: 14 / Seq: 32 (F)	230-FABRICATION - WEIDNER REMOVE ANNEAL BRACING AND PREPARE PANEL FOR RE-STRIKE / FINAL FORMING. ENSURE ALL WELDS ARE COMPLETLY REMOVED AND BLENDED FLUSH AND SMOOTH TO THE BASE MATERIAL. USE CAUTION TO AVOID GOUGES and/or HEAVY SCRATCHES ON THE PANEL SURFACES.	1.00	1.00	1.00	SE121-001P / A	
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	
		NDT Count: 0	WPS Count: 0			
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	
Sub: 14 / Seq: 35 (F)	805-INPROCESS INSPECTION - PLA VISUAL INSPECT SURFACE FOR DAMAGE, PITTING, GOUGES, SCRAPES ETC..... ON THE INSIDE (CONCAVE SURFACE), LOOK FOR ANY SURFACE DEFECTS THAT WILL INTERFERE WITH ACHIEVING THE REQUIRED 32 MICRO-INCH FINISH REQUIEMENT. ON THE OUTSIDE (CONVEX SURFACE), VERIFY THE SURFACE FINISH STILL MEETS THE REQUIREMENTS OF ASTM B 443-00. NOTIFY ENGINEERING (DOUG McCORKLE) FOR CONCURRENCE VERIFY MAGNETIC PERMEABILITY AND RECORD I.D.C. DATA Part Number: SE121-001P-2 PANEL 1 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A	
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2	
		NDT Count: 0	WPS Count: 0			

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev		
Sub: 14 / Seq: 40 (F)	341-PACIFIC 750 LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PREFORMED PANEL INTO THE DIE SET. "RE-STRIKE" HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE # _____. PANEL TO GAGE GAP TOLERANCE: .08" MAX. VERIFY PROFILE TO INSPECTION GAGE # _____. GAP TOLERANCE: .08" MAX. NOTIFY INSPECTOR FOR Q/A IDC VERIFICATION LAYOUT AND PRICK-PUNCH TRIM-LINES ON THE PANEL ESTABLISHED FROM THE MACHINED PERIMETER OF THE INSPECTION GAGE.	1.00	1.00	1.00	SE121-001P / A		
Part Number: SE121-001P-2 PANEL 1 Part Description: DIE FORMED PANEL							
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev		
Sub: 14 / Seq: 50 (F)	260-SANDBLAST SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev		
Sub: 14 / Seq: 60 (F)	230-FABRICATION - WEIDNER TRIM PERIMETER TO PROVIDED TRIM-LINES. NOTE THAT INSTALLING THE WELD PREP IS NOT REQUIRED AT THIS STAGE (ADDITIONAL FITTING / TRIMMING MAY BE REQUIRED AT INSTALLATION) SAND AND POLISH THE INSIDE SURFACE 100% TO ACHIEVE A 32 MICRO SURFACE FINISH (WITH THE EXCEPTION OF THE WELDING / TRIMMING ZONES). CLEAN PANEL PER CLEANING PROCEDURE PP475.	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev		
Sub: 14 / Seq: 70 (F)	805-INPROCESS INSPECTION - PLA VERIFY PROFILE TO INSPECTION GAGE # _____. GAP TOLERANCE: .08" MAX. PERIMETER SHOULD FALL WITHIN .03" OF GAGE PERIMETER. INSPECT AND RECORD INTERIOR SIDE SURFACE FINISH. INSPECT AND RECORD MAGNETIC PERMEABLY. Test Certification: DIMENSIONAL INSPECTION MAP Rev: Part Number: SE121-001P-2 PANEL 1 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 3	Dwg Count: 1	Pgm Count: 0	QAP Count: 3	NDT Count: 0	WPS Count: 0

Sub ID	Part ID	Qty	Drawing ID / Rev
15	SE121-001P-2 PANEL # 2	1	/
			Parent Sub:1 Op:10

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
-----------	----------	--------	----------	-------	------------------

Workorder	Part ID	Qty	Drawing ID / Rev	Engineer	
64880/1		1	SE121 / A	BLUE/DOUG MCCORKLE	
Sub: 15 / Seq: 10 (F)	410-BURNOUT TABLE	1.00	1.00	1.00	SE121-001P / A
	1. PRIOR TO BEGINNING WORK, CONTACT Q/A TO PERFORM A SERIES OF MATERIAL THICKNESS AND MAGNETIC PERMEABILITY TESTS ON THE RAW MATEIRAL (PRIOR TO MATERIAL PROCESSING AND HANDLING BY MTM). 2. NEST AND PROGRAM PER PROVIDED GEOMETRY. 3. BURNOUT AND CLEANUP PANEL PER NESTING / PROGRAM. 4. CLEANUP EDGES / RADIUS CORNERS (.03" MIN. RAD). ENSURE ALL DROSS AND RE-CAST LAYER IS REMOVED. ENSURE THE CUT SURFACE IS BLENDED SMOOTH. 5. NOTIFY Q/A FOR VERIFICATION PRIOR TO MOVING TO THE NEXT WORK CENTER. Specification: ASTM A800 Rev: 91 Part Number: SE121-001P-2 PANEL 2 Customer: PPPL Part Description: DIE FORMED PANEL Specification: ASTM B443 Rev: 93				

Piece #	Part ID	IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 3	NDT Count: 0	WPS Count: 0
	Qty	Drawing ID / Rev	Vendor	Dimensions			
10	INCONEL 625_5-PLATE,NICKEL ALLOY .375" THK	1,544.2			1810	35.07*44.03	
(F)	Vendor Part ID: INCONEL 625_5 INCONEL 625 (UNS N06625) PER ASTM B 443-00 ANNEALED MAGNETIC PERMEABILITY SHALL NOT EXCEED 1.00 (REF. ASTM A800). SURFACE MUST BE PROTECTED FROM CONTACT WITH IRON AND IRON ALLOY MATERIALS CERTS & MILL TEST REPORTS REQ'D WITH SHIPMENT. Material Certification: Part Number: SE121-001P-2 PANEL 2 Part Description: DIE FORMED PANEL						

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	
Sub: 15 / Seq: 15 (F)	805-INPROCESS INSPECTION - PLA	1.00	1.00	1.00	SE121-001P / A	
	INSPECT BLANK SIZE PER DRAWING VERIFY EDGES ARE SMOOTH AND CORNERS HAVE RADII APPLIED PER PREVIOUS SEQUENCE. INSPECT MATERIAL THICKNESS PER ASTM B443 VISUAL INSPECT SURFACE FINISH PER ASTM B443 INSPECT MAGNETIC PERMEABILITY PER ASTM A800 RECORD IDC DATA APPLY PROTECTIVE PLASTIC TO BOTH SIDES OF PANEL (AVAILABLE IN WIP STORAGE) Specification: ASTM A800 Rev: 91 Part Number: SE121-001P-2 PANEL 2 Part Description: DIE FORMED PANEL Customer: PPPL Specification: ASTM B443 Rev: 93					
	IDC Count : 3	Dwg Count: 1	Pgm Count: 0	QAP Count: 5	NDT Count: 0	WPS Count: 0

Workorder	Part ID	Qty	Drawing ID / Rev	Engineer		
64880/1		1	SE121 / A	BLUE/DOUG MCCORKLE		
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	
Sub: 15 / Seq: 18 (F)	415-ROLLING/SHEAR/BRAKE PRESS ROLL PANEL BLANK INTO A CONE PER PROCESS DRAWING. ENSURE PLATE ROLLS ARE COMPLETELY CLEAN AND FREE OF DIRT, GRIME, FOREIGN MATTER, AND RAISED METAL PRIOR TO ROLLING. ENSURE THE PANEL BLANKS ARE PROTECTED WITH PLASTIC SHEET DURING THE ENTIRE PROCESS. NOTIFY ENGINEERING (DOUG McCORKLE) PRIOR TO PROCEEDING.	1.00	1.00	1.00	SE121-001P / A	
	IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	
Sub: 15 / Seq: 20 (F)	341-PACIFIC 750 LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PANEL BLANK (OR CONE) INTO THE DIE SET. HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE # _____. PANEL TO GAGE GAP TOLERANCE: .08" MAX. NOTIFY Q/A FOR PROFILE IDC VERIFICATION ENSURE THE PANEL MATERIAL EXTENDS BEYOND THE PERIMETER OF THE TRIM-LINES OF THE GAGE BY AT LEAST 1" (TO PROVIDE ADEQUATE STOCK ALLOWANCE FOR RE-POSITIONING, RE-STRIKING, AND ACCURATE TRIMMING). Part Number: SE121-001P-2 PANEL 2 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A	
	IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	
Sub: 15 / Seq: 25 (F)	260-SANDBLAST SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.	1.00	1.00	1.00	SE121-001P / A	
	IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	
Sub: 15 / Seq: 27 (F)	230-FABRICATION - WEIDNER INSTALL AND WELD ANNEAL BRACING IN PLACE PER ENGINEERING SKETCH ENSURE PART IS CLEAN AND READY FOR SOLUTION ANNEAL CYCLE	1.00	1.00	1.00	SE121-001P / A	
	IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 1
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 15 / Seq: 30 (F)	520-SUBLET, EXOTIC HEAT TREAT SOLUTION ANNEAL FORMED PANEL PER THE FOLLOWING: ATTACH A MINIMUM OF THREE EQUALLY SPACED THERMOCOUPLES TO THE FORMED PANEL CHARGE FURNACE AND HEAT PART UNTIL THERMOCOUPLE READINGS ARE WITHIN 1900 +/-15F. HOLD PART TEMPERATURE AT 1900 DEGREES F. (+/- 15 DEGREES) HOLD FOR 45 MINUTES (+/ 5 MINUTES) RAPID COOL (VIA. WATER QUENCHING OR FORCED AIR CIRCULATION) TO 1000 DEGREES F. OPEN AIR COOL TO AMBIENT TEMP. Specification: AMS2774 Rev: JUL95 Certification: H/T CERTIFICATE Part Number: SE121-001P-2 PANEL 2	1.00	1.00	1.00	SE121-001P / A	THRML TR/NA SA

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Part Description: DIE FORMED PANEL
Customer: PPPL
Furnace charts: FURNACE CHART

IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 6 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 15 / Seq: 32 (U)	230-FABRICATION - WEIDNER REMOVE ANNEAL BRACING AND PREPARE PANEL FOR RE-STRIKE / FINAL FORMING. ENSURE ALL WELDS ARE COMPLETELY REMOVED AND BLENDED FLUSH AND SMOOTH TO THE BASE MATERIAL. USE CAUTION TO AVOID GOUGES and/or HEAVY SCRATCHES ON THE PANEL SURFACES.	1.00	1.00	1.00	SE121-001P / A
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 15 / Seq: 35 (F)	805-INPROCESS INSPECTION - PLA VISUAL INSPECT SURFACE FOR DAMAGE, PITTING, GOUGES, SCRAPES ETC..... NOTIFY ENGINEERING (DOUG McCORKLE) FOR CONCURRENCE VERIFY MAGNETIC PERMEABILITY AND RECORD I.D.C. DATA Part Number: SE121-001P-2 PANEL 2 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 15 / Seq: 40 (F)	341-PACIFIC 750 LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PREFORMED PANEL INTO THE DIE SET. "RE-STRIKE" HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE # _____. PANEL TO GAGE GAP TOLERANCE: .08" MAX. VERIFY PROFILE TO INSPECTION GAGE # _____. GAP TOLERANCE: .08" MAX. NOTIFY INSPECTOR FOR Q/A IDC VERIFICATION LAYOUT AND PRICK-PUNCH TRIM-LINES ON THE PANEL ESTABLISHED FROM THE MACHINED PERIMETER OF THE INSPECTION GAGE. Part Number: SE121-001P-2 PANEL 2 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 15 / Seq: 50 (F)	260-SANDBLAST SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.	1.00	1.00	1.00	SE121-001P / A
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 15 / Seq: 60 (F)	230-FABRICATION - WEIDNER TRIM PERIMETER TO PROVIDED TRIM-LINES. NOTE THAT INSTALLING THE WELD PREP IS NOT REQUIRED AT THIS STAGE (ADDITIONAL FITTING / TRIMMING MAY BE REQUIRED AT INSTALLATION)	1.00	1.00	1.00	SE121-001P / A

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

SAND AND POLISH THE INSIDE SURFACE 100% TO ACHIEVE A 32 MICRO SURFACE FINISH (WITH THE EXCEPTION OF THE WELDING / TRIMMING ZONES).
CLEAN PANEL PER CLEANING PROCEDURE PP475.

IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 15 / Seq: 70 (F)	805-INPROCESS INSPECTION - PLA VERIFY PROFILE TO INSPECTION GAGE #_____. GAP TOLERANCE: .08" MAX. PERIMETER SHOULD FALL WITHIN .03" OF GAGE PERIMETER. INSPECT AND RECORD INTERIOR SIDE SURFACE FINISH. INSPECT AND RECORD MAGNETIC PERMEABILITY. Test Certification: DIMENSIONAL INSPECTION MAP Rev: Part Number: SE121-001P-2 PANEL 2 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A
		IDC Count : 3	Dwg Count: 1	Pgm Count: 0	QAP Count: 3 NDT Count: 0 WPS Count: 0

Sub ID	Part ID	Qty	Drawing ID / Rev
16	SE121-001P-2 PANEL # 3	1	/
		Parent Sub:1 Op:10	

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 16 / Seq: 10 (F)	410-BURNOUT TABLE 1. PRIOR TO BEGINNING WORK, CONTACT Q/A TO PERFORM A SERIES OF MATERIAL THICKNESS AND MAGNETIC PERMEABILITY TESTS ON THE RAW MATEIRAL (PRIOR TO MATERIAL PROCESSING AND HANDLING BY MTM). 2. NEST AND PROGRAM PER PROVIDED GEOMETRY. 3. BURNOUT AND CLEANUP PANEL PER NESTING / PROGRAM. 4. CLEANUP EDGES / RADIUS CORNERS (.03" MIN. RAD). ENSURE ALL DROSS AND RE-CAST LAYER IS REMOVED. ENSURE THE CUT SURFACE IS BLENDED SMOOTH. 5. NOTIFY Q/A FOR VERIFICATION PRIOR TO MOVING TO THE NEXT WORK CENTER. Specification: ASTM A800 Rev: 91 Part Number: SE121-001P-2 PANEL 3 Part Description: DIE FORMED PANEL Customer: PPPL Specification: ASTM B443 Rev: 93	1.00	1.00	1.00	SE121-001P / A
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 3 NDT Count: 0 WPS Count: 0

Piece #	Part ID	Qty	Drawing ID / Rev	Vendor	Dimensions
10	INCONEL 625_5-PLATE,NICKEL ALLOY .375" THK Vendor Part ID: INCONEL 625_5	3,865.9		1810	49.85*77.55
(F)	INCONEL 625 (UNS N06625) PER ASTM B 443-00 ANNEALED MAGNETIC PERMEABILITY SHALL NOT EXCEED 1.00 (REF. ASTM A800). SURFACE MUST BE PROTECTED FROM CONTACT WITH IRON AND IRON ALLOY MATERIALS CERTS & MILL TEST REPORTS REQ'D WITH SHIPMENT. Material Certification: Part Number: SE121-001P-2 PANEL 3 Part Description: DIE FORMED PANEL				

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev					
Sub: 16 / Seq: 15 (F)	805-INPROCESS INSPECTION - PLA INSPECT BLANK SIZE PER DRAWING VERIFY EDGES ARE SMOOTH AND CORNERS HAVE RADII APPLIED PER PREVIOUS SEQUENCE. INSPECT MATERIAL THICKNESS PER ASTM B443 VISUAL INSPECT SURFACE FINISH PER ASTM B443 INSPECT MAGNETIC PERMEABILITY PER ASTM A800 RECORD IDC DATA APPLY PROTECTIVE PLASTIC TO BOTH SIDES OF PANEL (AVAILABLE IN WIP STORAGE) Specification: ASTM A800 Rev: 91 Part Number: SE121-001P-2 PANEL 3 Part Description: DIE FORMED PANEL Customer: PPPL Specification: ASTM B443 Rev: 93	1.00	1.00	1.00	SE121-001P / A					
			IDC Count : 3	Dwg Count: 1	Pgm Count: 0	QAP Count: 5	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev					
Sub: 16 / Seq: 18 (F)	415-ROLLING/SHEAR/BRAKE PRESS ROLL PANEL BLANK INTO A CONE PER PROCESS DRAWING. ENSURE PLATE ROLLS ARE COMPLETELY CLEAN AND FREE OF DIRT, GRIME, FOREIGN MATTER, AND RAISED METAL PRIOR TO ROLLING. ENSURE THE PANEL BLANKS ARE PROTECTED WITH PLASTIC SHEET DURING THE ENTIRE PROCESS. NOTIFY ENGINEERING (DOUG McCORKLE) PRIOR TO PROCEEDING.	1.00	1.00	1.00	SE121-001P / A					
			IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev					
Sub: 16 / Seq: 20 (F)	341-PACIFIC 750 LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PANEL BLANK (OR CONE) INTO THE DIE SET. HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE # _____. PANEL TO GAGE GAP TOLERANCE: .08" MAX. NOTIFY Q/A FOR PROFILE IDC VERIFICATION ENSURE THE PANEL MATERIAL EXTENDS BEYOND THE PERIMETER OF THE TRIM-LINES OF THE GAGE BY AT LEAST 1" (TO PROVIDE ADEQUATE STOCK ALLOWANCE FOR RE-POSITIONING, RE-STRIKING, AND ACCURATE TRIMMING). Part Number: SE121-001P-2 PANEL 3 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A					
			IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev					
Sub: 16 / Seq: 25	260-SANDBLAST	1.00	1.00	1.00	SE121-001P / A					

Workorder	Part ID	Qty	Drawing ID / Rev	Engineer		
64880/1		1	SE121 / A	BLUE/DOUG MCCORKLE		
(F)	SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.					
	IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0 NDT Count: 0 WPS Count: 0		
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 16 / Seq: 27	230-FABRICATION - WEIDNER	1.00	1.00	1.00	SE121-001P / A	THRML TR/NA SA
(F)	INSTALL AND WELD ANNEAL BRACING IN PLACE PER ENGINEERING SKETCH ENSURE PART IS CLEAN AND READY FOR SOLUTION ANNEAL CYCLE					
	IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 1
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 16 / Seq: 30	520-SUBLET, EXOTIC HEAT TREAT	1.00	1.00	1.00	SE121-001P / A	THRML TR/NA SA
(F)	SOLUTION ANNEAL FORMED PANEL PER THE FOLLOWING: ATTACH A MINIMUM OF THREE EQUALLY SPACED THERMOCOUPLES TO THE FORMED PANEL CHARGE FURNACE AND HEAT PART UNTIL THERMOCOUPLE READINGS ARE WITHIN 1900 +/-15F. HOLD PART TEMPERATURE AT 1900 DEGREES F. (+/- 15 DEGREES) HOLD FOR 45 MINUTES (+/ 5 MINUTES) RAPID COOL (VIA. WATER QUENCHING OR FORCED AIR CIRCULATION) TO 1000 DEGREES F. OPEN AIR COOL TO AMBIENT TEMP. Specification: AMS2774 Rev: JUL95 Certification: H/T CERTIFICATE Part Number: SE121-001P-2 PANEL 3 Part Description: DIE FORMED PANEL Customer: PPPL Furnace charts: FURNACE CHART					
	IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 6	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 16 / Seq: 32	230-FABRICATION - WEIDNER	1.00	1.00	1.00	SE121-001P / A	
(U)	REMOVE ANNEAL BRACING AND PREPARE PANEL FOR RE-STRIKE / FINAL FORMING. ENSURE ALL WELDS ARE COMPLETELY REMOVED AND BLENDED FLUSH AND SMOOTH TO THE BASE MATERIAL. USE CAUTION TO AVOID GOUGES and/or HEAVY SCRATCHES ON THE PANEL SURFACES.					
	IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 16 / Seq: 35	805-INPROCESS INSPECTION - PLA	1.00	1.00	1.00	SE121-001P / A	
(F)	VISUAL INSPECT SURFACE FOR DAMAGE, PITTING, GOUGES, SCRAPES ETC..... NOTIFY ENGINEERING (DOUG McCORKLE) FOR CONCURRENCE VERIFY MAGNETIC PERMEABILITY AND RECORD I.D.C. DATA Part Number: SE121-001P-2 PANEL 3 Part Description: DIE FORMED PANEL					
	IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 16 / Seq: 40	341-PACIFIC 750	1.00	1.00	1.00	SE121-001P / A	
(F)	LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PREFORMED PANEL INTO THE DIE SET.					

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

"RE-STRIKE" HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE #_____.
 PANEL TO GAGE GAP TOLERANCE: .08" MAX.
 VERIFY PROFILE TO INSPECTION GAGE #_____. GAP TOLERANCE: .08" MAX.
 NOTIFY INSPECTOR FOR Q/A IDC VERIFICATION
 LAYOUT AND PRICK-PUNCH TRIM-LINES ON THE PANEL ESTABLISHED FROM THE MACHINED PERIMETER OF THE INSPECTION GAGE.

Part Number: SE121-001P-2 PANEL 3
 Part Description: DIE FORMED PANEL

IDC Count : 1 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 16 / Seq: 50 (F)	260-SANDBLAST SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.	1.00	1.00	1.00	SE121-001P / A
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 16 / Seq: 60 (F)	230-FABRICATION - WEIDNER TRIM PERIMETER TO PROVIDED TRIM-LINES. NOTE THAT INSTALLING THE WELD PREP IS NOT REQUIRED AT THIS STAGE (ADDITIONAL FITTING / TRIMMING MAY BE REQUIRED AT INSTALLATION) SAND AND POLISH THE INSIDE SURFACE 100% TO ACHIEVE A 32 MICRO SURFACE FINISH (WITH THE EXCEPTION OF THE WELDING / TRIMMING ZONES). CLEAN PANEL PER CLEANING PROCEDURE PP475.	1.00	1.00	1.00	SE121-001P / A
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 16 / Seq: 70 (F)	805-INPROCESS INSPECTION - PLA VERIFY PROFILE TO INSPECTION GAGE #_____. GAP TOLERANCE: .08" MAX. PERIMETER SHOULD FALL WITHIN .03" OF GAGE PERIMETER. INSPECT AND RECORD INTERIOR SIDE SURFACE FINISH. INSPECT AND RECORD MAGNETIC PERMEABILIY. Test Certification: DIMENSIONAL INSPECTION MAP Rev: Part Number: SE121-001P-2 PANEL 3 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A
		IDC Count : 3	Dwg Count: 1	Pgm Count: 0	QAP Count: 3 NDT Count: 0 WPS Count: 0

Sub ID	Part ID	Qty	Drawing ID / Rev
17	SE121-001P-2 PANEL # 4	1	/
			Parent Sub:1 Op:10

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 17 / Seq: 10 (F)	410-BURNOUT TABLE 1. PRIOR TO BEGINNING WORK, CONTACT Q/A TO PERFORM A SERIES OF MATERIAL THICKNESS AND MAGNETIC PERMEABILITY TESTS ON THE RAW MATEIRAL (PRIOR TO MATERIAL PROCESSING AND HANDLING BY MTM). 2. NEST AND PROGRAM PER PROVIDED GEOMETRY. 3. BURNOUT AND CLEANUP PANEL PER NESTING / PROGRAM. 4. CLEANUP EDGES / RADIUS CORNERS (.03" MIN. RAD). ENSURE ALL DROSS AND RE-CAST LAYER IS REMOVED. ENSURE THE CUT SURFACE IS BLENDED SMOOTH.	1.00	1.00	1.00	SE121-001P / A

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 17 / Seq: 20 (F)	341-PACIFIC 750 LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PANEL BLANK (OR CONE) INTO THE DIE SET. HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE # _____. PANEL TO GAGE GAP TOLERANCE: .08" MAX. NOTIFY Q/A FOR PROFILE IDC VERIFICATION ENSURE THE PANEL MATERIAL EXTENDS BEYOND THE PERIMETER OF THE TRIM-LINES OF THE GAGE BY AT LEAST 1" (TO PROVIDE ADEQUATE STOCK ALLOWANCE FOR RE-POSITIONING, RE-STRIKING, AND ACCURATE TRIMMING). Part Number: SE121-001P-2 PANEL 4 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A

IDC Count : 1 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 17 / Seq: 25 (F)	260-SANDBLAST SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.	1.00	1.00	1.00	SE121-001P / A

IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
Sub: 17 / Seq: 27 (F)	230-FABRICATION - WEIDNER INSTALL AND WELD ANNEAL BRACING IN PLACE PER ENGINEERING SKETCH ENSURE PART IS CLEAN AND READY FOR SOLUTION ANNEAL CYCLE	1.00	1.00	1.00	SE121-001P / A

IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 1

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID
Sub: 17 / Seq: 30 (F)	520-SUBLET, EXOTIC HEAT TREAT SOLUTION ANNEAL FORMED PANEL PER THE FOLLOWING: ATTACH A MINIMUM OF THREE EQUALLY SPACED THERMOCOUPLES TO THE FORMED PANEL CHARGE FURNACE AND HEAT PART UNTIL THERMOCOUPLE READINGS ARE WITHIN 1900 +/-15F. HOLD PART TEMPERATURE AT 1900 DEGREES F. (+/- 15 DEGREES) HOLD FOR 45 MINUTES (+/ 5 MINUTES) RAPID COOL (VIA. WATER QUENCHING OR FORCED AIR CIRCULATION) TO 1000 DEGREES F. OPEN AIR COOL TO AMBIENT TEMP. Specification: AMS2774 Rev: JUL95 Certification: H/T CERTIFICATE Part Number: SE121-001P-2 PANEL 4 Part Description: DIE FORMED PANEL Customer: PPPL Furnace charts: FURNACE CHART	1.00	1.00	1.00	SE121-001P / A	THRML TR/NA SA

IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 6 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev
------------------	-----------------	---------------	-----------------	--------------	-------------------------

Workorder	Part ID	Qty	Drawing ID / Rev	Engineer			
64880/1		1	SE121 / A	BLUE/DOUG MCCORKLE			
Sub: 17 / Seq: 32 (U)	230-FABRICATION - WEIDNER REMOVE ANNEAL BRACING AND PREPARE PANEL FOR RE-STRIKE / FINAL FORMING. ENSURE ALL WELDS ARE COMPLETELY REMOVED AND BLENDED FLUSH AND SMOOTH TO THE BASE MATERIAL. USE CAUTION TO AVOID GOUGES and/or HEAVY SCRATCHES ON THE PANEL SURFACES.	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev		
Sub: 17 / Seq: 35 (F)	805-INPROCESS INSPECTION - PLA VISUAL INSPECT SURFACE FOR DAMAGE, PITTING, GOUGES, SCRAPES ETC.... NOTIFY ENGINEERING (DOUG MCCORKLE) FOR CONCURRENCE VERIFY MAGNETIC PERMEABILITY AND RECORD I.D.C. DATA Part Number: SE121-001P-2 PANEL 4 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev		
Sub: 17 / Seq: 40 (F)	341-PACIFIC 750 LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PREFORMED PANEL INTO THE DIE SET. "RE-STRIKE" HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE # _____. PANEL TO GAGE GAP TOLERANCE: .08" MAX. VERIFY PROFILE TO INSPECTION GAGE # _____. GAP TOLERANCE: .08" MAX. NOTIFY INSPECTOR FOR Q/A IDC VERIFICATION LAYOUT AND PRICK-PUNCH TRIM-LINES ON THE PANEL ESTABLISHED FROM THE MACHINED PERIMETER OF THE INSPECTION GAGE. Part Number: SE121-001P-2 PANEL 4 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev		
Sub: 17 / Seq: 50 (F)	260-SANDBLAST SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev		
Sub: 17 / Seq: 60 (F)	230-FABRICATION - WEIDNER TRIM PERIMETER TO PROVIDED TRIM-LINES. NOTE THAT INSTALLING THE WELD PREP IS NOT REQUIRED AT THIS STAGE (ADDITIONAL FITTING / TRIMMING MAY BE REQUIRED AT INSTALLATION) SAND AND POLISH THE INSIDE SURFACE 100% TO ACHIEVE A 32 MICRO SURFACE FINISH (WITH THE EXCEPTION OF THE WELDING / TRIMMING ZONES). CLEAN PANEL PER CLEANING PROCEDURE PP475.	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev		
Sub: 17 / Seq: 70	805-INPROCESS INSPECTION - PLA	1.00	1.00	1.00	SE121-001P / A		

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

(F) VERIFY PROFILE TO INSPECTION GAGE #_____. GAP TOLERANCE: .08" MAX. PERIMETER SHOULD FALL WITHIN .03" OF GAGE PERIMETER.
INSPECT AND RECORD INTERIOR SIDE SURFACE FINISH.
INSPECT AND RECORD MAGNETIC PERMEABILITY.
Test Certification: DIMENSIONAL INSPECTION MAP Rev:
Part Number: SE121-001P-2 PANEL 4
Part Description: DIE FORMED PANEL

IDC Count : 3 Dwg Count: 1 Pgm Count: 0 QAP Count: 3 NDT Count: 0 WPS Count: 0

Sub ID 18	Part ID SE121-001P-2 PANEL # 5	Qty 1	Drawing ID / Rev / Parent Sub:1 Op:10
---------------------	--	-----------------	--

Operation Sub: 18 / Seq: 10	Resource 410-BURNOUT TABLE	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A
---------------------------------------	--------------------------------------	-----------------------	-------------------------	----------------------	---

(F) 1. PRIOR TO BEGINNING WORK, CONTACT Q/A TO PERFORM A SERIES OF MATERIAL THICKNESS AND MAGNETIC PERMEABILITY TESTS ON THE RAW MATEIRAL (PRIOR TO MATERIAL PROCESSING AND HANDLING BY MTM).
2. NEST AND PROGRAM PER PROVIDED GEOMETRY.
3. BURNOUT AND CLEANUP PANEL PER NESTING / PROGRAM.
4. CLEANUP EDGES / RADIUS CORNERS (.03" MIN. RAD). ENSURE ALL DROSS AND RE-CAST LAYER IS REMOVED. ENSURE THE CUT SURFACE IS BLENDED SMOOTH.
5. NOTIFY Q/A FOR VERIFICATION PRIOR TO MOVING TO THE NEXT WORK CENTER.
Specification: ASTM A800 Rev: 91
Part Number: SE121-001P-2 PANEL 5
Part Description: DIE FORMED PANEL
Customer: PPPL
Specification: ASTM B443 Rev: 93

IDC Count : 1 Dwg Count: 1 Pgm Count: 0 QAP Count: 3 NDT Count: 0 WPS Count: 0

Piece # 10	Part ID INCONEL 625_5-PLATE,NICKEL ALLOY .375" THK	Qty 2,856.9	Drawing ID / Rev	Vendor 1810	Dimensions 39.90*71.60
----------------------	--	-----------------------	-------------------------	-----------------------	----------------------------------

(F) INCONEL 625 (UNS N06625) PER ASTM B 443-00
ANNEALED
MAGNETIC PERMEABILITY SHALL NOT EXCEED 1.00 (REF. ASTM A800).
SURFACE MUST BE PROTECTED FROM CONTACT WITH IRON AND IRON ALLOY MATERIALS
CERTS & MILL TEST REPORTS REQ'D WITH SHIPMENT.

Material Certification:
Part Number: SE121-001P-2 PANEL 5
Part Description: DIE FORMED PANEL

Operation Sub: 18 / Seq: 15	Resource 805-INPROCESS INSPECTION - PLA	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A
---------------------------------------	---	-----------------------	-------------------------	----------------------	---

(F) INSPECT BLANK SIZE PER DRAWING
VERIFY EDGES ARE SMOOTH AND CORNERS HAVE RADII APPLIED PER PREVIOUS SEQUENCE.

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

INSPECT MATERIAL THICKNESS PER ASTM B443
 VISUAL INSPECT SURFACE FINISH PER ASTM B443
 INSPECT MAGNETIC PERMEABILITY PER ASTM A800
 RECORD IDC DATA
 APPLY PROTECTIVE PLASTIC TO BOTH SIDES OF PANEL
 (AVAILABLE IN WIP STORAGE)
 Specification: ASTM A800 Rev: 91
 Part Number: SE121-001P-2 PANEL 5
 Part Description: DIE FORMED PANEL
 Customer: PPPL
 Specification: ASTM B443 Rev: 93

IDC Count : 3 Dwg Count: 1 Pgm Count: 0 QAP Count: 5 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 18 / Seq: 18 (F)	415-ROLLING/SHEAR/BRAKE PRESS	1.00	1.00	1.00	SE121-001P / A				
	ROLL PANEL BLANK INTO A CONE PER PROCESS DRAWING. ENSURE PLATE ROLLS ARE COMPLETELY CLEAN AND FREE OF DIRT, GRIME, FOREIGN MATTER, AND RAISED METAL PRIOR TO ROLLING. ENSURE THE PANEL BLANKS ARE PROTECTED WITH PLASTIC SHEET DURING THE ENTIRE PROCESS. NOTIFY ENGINEERING (DOUG McCORKLE) PRIOR TO PROCEEDING.								
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 18 / Seq: 20 (F)	341-PACIFIC 750	1.00	1.00	1.00	SE121-001P / A				
	LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PANEL BLANK (OR CONE) INTO THE DIE SET. HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE # _____. PANEL TO GAGE GAP TOLERANCE: .08" MAX. NOTIFY Q/A FOR PROFILE IDC VERIFICATION ENSURE THE PANEL MATERIAL EXTENDS BEYOND THE PERIMETER OF THE TRIM-LINES OF THE GAGE BY AT LEAST 1" (TO PROVIDE ADEQUATE STOCK ALLOWANCE FOR RE-POSITIONING, RE-STRIKING, AND ACCURATE TRIMMING). Part Number: SE121-001P-2 PANEL 5 Part Description: DIE FORMED PANEL								
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 18 / Seq: 25 (F)	260-SANDBLAST	1.00	1.00	1.00	SE121-001P / A				
	SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.								
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 18 / Seq: 27 (F)	230-FABRICATION - WEIDNER	1.00	1.00	1.00	SE121-001P / A				
	INSTALL AND WELD ANNEAL BRACING IN PLACE PER ENGINEERING SKETCH								

Workorder	Part ID	Qty	Drawing ID / Rev	Engineer			
64880/1		1	SE121 / A	BLUE/DOUG MCCORKLE			
ENSURE PART IS CLEAN AND READY FOR SOLUTION ANNEAL CYCLE							
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 1
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID	
Sub: 18 / Seq: 30 (F)	520-SUBLET, EXOTIC HEAT TREAT SOLUTION ANNEAL FORMED PANEL PER THE FOLLOWING: ATTACH A MINIMUM OF THREE EQUALLY SPACED THERMOCOUPLES TO THE FORMED PANEL CHARGE FURNACE AND HEAT PART UNTIL THERMOCOUPLE READINGS ARE WITHIN 1900 +/-15F. HOLD PART TEMPERATURE AT 1900 DEGREES F. (+/- 15 DEGREES) HOLD FOR 45 MINUTES (+/ 5 MINUTES) RAPID COOL (VIA. WATER QUENCHING OR FORCED AIR CIRCULATION) TO 1000 DEGREES F. OPEN AIR COOL TO AMBIENT TEMP. Specification: AMS2774 Rev: JUL95 Certification: H/T CERTIFICATE Part Number: SE121-001P-2 PANEL 5 Part Description: DIE FORMED PANEL Customer: PPPL Furnace charts: FURNACE CHART	1.00	1.00	1.00	SE121-001P / A	THRML TR/NA SA	
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 6	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID	
Sub: 18 / Seq: 32 (U)	230-FABRICATION - WEIDNER REMOVE ANNEAL BRACING AND PREPARE PANEL FOR RE-STRIKE / FINAL FORMING. ENSURE ALL WELDS ARE COMLPETELY REMOVED AND BLENDED FLUSH AND SMOOTH TO THE BASE MATERIAL. USE CAUTION TO AVOID GOUGES and/or HEAVY SCRATCHES ON THE PANEL SURFACES.	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID	
Sub: 18 / Seq: 35 (F)	805-INPROCESS INSPECTION - PLA VISUAL INSPECT SURFACE FOR DAMAGE, PITTING, GOUGES, SCRAPES ETC..... NOTIFY ENGINEERING (DOUG McCORKLE) FOR CONCURRENCE VERIFY MAGNETIC PERMEABILITY AND RECORD I.D.C. DATA Part Number: SE121-001P-2 PANEL 5 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A		
		IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	Service ID	
Sub: 18 / Seq: 40 (F)	341-PACIFIC 750 LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC.... LOAD THE PREFORMED PANEL INTO THE DIE SET. "RE-STRIKE" HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE #_____ PANEL TO GAGE GAP TOLERANCE: .08" MAX. VERIFY PROFILE TO INSPECTION GAGE #_____. GAP TOLERANCE: .08" MAX. NOTIFY INSPECTOR FOR Q/A IDC VERIFICATION LAYOUT AND PRICK-PUNCH TRIM-LINES ON THE PANEL ESTABLISHED FROM THE MACHINED PERIMETER OF THE INSPECTION GAGE.	1.00	1.00	1.00	SE121-001P / A		

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Part Number: SE121-001P-2 PANEL 5
Part Description: DIE FORMED PANEL

IDC Count : 1 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 18 / Seq: 50 (F)	260-SANDBLAST SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.	1.00	1.00	1.00	SE121-001P / A				
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 18 / Seq: 60 (F)	230-FABRICATION - WEIDNER TRIM PERIMETER TO PROVIDED TRIM-LINES. NOTE THAT INSTALLING THE WELD PREP IS NOT REQUIRED AT THIS STAGE (ADDITIONAL FITTING / TRIMMING MAY BE REQUIRED AT INSTALLATION) SAND AND POLISH THE INSIDE SURFACE 100% TO ACHIEVE A 32 MICRO SURFACE FINISH (WITH THE EXCEPTION OF THE WELDING / TRIMMING ZONES). CLEAN PANEL PER CLEANING PROCEDURE PP475.	1.00	1.00	1.00	SE121-001P / A				
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 18 / Seq: 70 (F)	805-INPROCESS INSPECTION - PLA VERIFY PROFILE TO INSPECTION GAGE #_____. GAP TOLERANCE: .08" MAX. PERIMETER SHOULD FALL WITHIN .03" OF GAGE PERIMETER. INSPECT AND RECORD INTERIOR SIDE SURFACE FINISH. INSPECT AND RECORD MAGNETIC PERMEABILIY. Test Certification: DIMENSIONAL INSPECTION MAP Rev: Part Number: SE121-001P-2 PANEL 5 Part Description: DIE FORMED PANEL	1.00	1.00	1.00	SE121-001P / A				
		IDC Count : 3	Dwg Count: 1	Pgm Count: 0	QAP Count: 3	NDT Count: 0	WPS Count: 0		

Sub ID	Part ID	Qty	Drawing ID / Rev
24	SURFACE FINISH TESTING TEST P	1	/
			Parent Sub:1 Op:10

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 24 / Seq: 10 (C)	410-BURNOUT TABLE BURNOUT TEST PLATES PER MATERIAL CARD. DEBURR AND SAND EDGES SMOOTH (WITH UNCONTAMINATED GRINDING WHEEL ONLY). FORWARD ONE PLATE TO ENGINEERING (DOUG McCORKLE) AND PROCESS THE OTHER PER THE FOLLOWING ROUTING STEPS.	1.00	1.00	1.00	SE121 / A				
		IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 1	NDT Count: 0	WPS Count: 0		

Piece #	Part ID	Qty	Drawing ID / Rev	Vendor	Dimensions
10 (C)	INCONEL 625_670-SHEET,NICKEL ALLOY .25" THK INCONEL 625 SHEET, .25" THICK PER AMS 5599. CERT AND MILL TEST REPORT REQ'D WITH SHIPMENT.	480.0			480

Material Certification: NONE REQ'D TEST SAMPLE

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 24 / Seq: 20 (R)	230-FABRICATION - WEIDNER SAND AND POLISH THE TEST PIECE (ONE SIDE) TO A 32 RA MICRO SURFACE FINISH	1.00	1.00	1.00	SE121 / A				
		IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 24 / Seq: 25 (R)	260-SANDBLAST MASK THE POLISHED SIDE AND BLAST THE OTHER SIDE WITH 180-220 GRIT VIRGIN ALUMINUM OXIDE.	1.00	1.00	1.00	SE121 / A				
	Drw N/A	IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 24 / Seq: 28 (R)	230-FABRICATION - WEIDNER CLEAN SAMPLE MATERIAL SURFACES PER THE FOLLOWING.....(cleaning specification being developed) WRAP THE PART IN PLASTIC FOAM.	1.00	1.00	1.00	SE121 / A				
	Drw N/A	IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 24 / Seq: 30 (R)	805-INPROCESS INSPECTION - PLA VERIFY THE FOLLOWING TEST SAMPLE ATTRIBUTES: SURFACE FINISH (PER ASME B46.1-1995) CLEANLINESS PER PP475. MAGNETIC PERMEABILITY (1.01 MAX) REPORT RESULTS TO ENGINEERING (DOUG McCORKLE).	1.00	1.00	1.00	SE121 / A				
		IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Sub ID	Part ID	Qty	Drawing ID / Rev
26	SE121-001P-2 TEST PANEL	1	/
			Parent Sub:1 Op:10

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 26 / Seq: 10 (F)	410-BURNOUT TABLE 1. PRIOR TO BEGINNING WORK, CONTACT Q/A TO PERFORM A SERIES OF MATERIAL THICKNESS AND MAGNETIC PERMEABILITY TESTS ON THE RAW MATEIRAL (PRIOR TO MATERIAL PROCESSING AND HANDLING BY MTM). 2. NEST AND PROGRAM PER PROVIDED GEOMETRY. 3. BURNOUT AND CLEANUP PANEL PER NESTING / PROGRAM. 4. CLEANUP EDGES / RADIUS CORNERS (.03" MIN. RAD). ENSURE ALL DROSS AND RE-CAST LAYER IS REMOVED. ENSURE THE CUT SURFACE IS BLENDED SMOOTH. 5. NOTIFY Q/A FOR VERIFICATION PRIOR TO MOVING TO THE NEXT WORK CENTER.	1.00	1.00	1.00	SE121-001P / A				
	Specification: ASTM A800 Rev: 91 Part Number: SE121-001P-2 TEST PANEL Part Description: DIE FORMED PANEL Customer: PPPL Specification: ASTM B443 Rev: 93	IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0		

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Piece # 10	Part ID INCONEL 625_5-PLATE,NICKEL ALLOY .375" THK Vendor Part ID: INCONEL 625_5	Qty 4,198.1	Drawing ID / Rev	Vendor 1810	Dimensions 54.97*76.37
----------------------	---	-----------------------	-------------------------	-----------------------	----------------------------------

(F) INCONEL 625 (UNS N06625) PER ASTM B 443-00 ANNEALED
MAGNETIC PERMEABILITY SHALL NOT EXCEED 1.00 (REF. ASTM A800).
SURFACE MUST BE PROTECTED FROM CONTACT WITH IRON AND IRON ALLOY MATERIALS
CERTS & MILL TEST REPORTS REQ'D WITH SHIPMENT.

Material Certification:
Part Number: SE121-2A
Part Description: DIE FORMED PANEL # 1

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev						
Sub: 26 / Seq: 15 (F)	805-INPROCESS INSPECTION - PLA INSPECT BLANK SIZE PER DRAWING VERIFY EDGES ARE SMOOTH AND CORNERS HAVE RADII APPLIED PER PREVIOUS SEQUENCE. INSPECT MATERIAL THICKNESS PER ASTM B443 VISUAL INSPECT SURFACE FINISH PER ASTM B443 INSPECT MAGNETIC PERMEABILITY PER ASTM A800 RECORD IDC DATA APPLY PROTECTIVE PLASTIC TO BOTH SIDES OF PANEL (AVAILABLE IN WIP STORAGE) Specification: ASTM A800 Rev: 91 Part Number: SE121-001P-2 TEST PANEL Part Description: DIE FORMED PANEL Customer: PPPL Specification: ASTM B443 Rev: 93	1.00	1.00	1.00	SE121-001P / A	IDC Count : 1	Dwg Count: 1	Pgm Count: 0	QAP Count: 5	NDT Count: 0	WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev						
Sub: 26 / Seq: 18 (F)	415-ROLLING/SHEAR/BRAKE PRESS ROLL PANEL BLANK INTO A CONE PER PROCESS DRAWING. ENSURE PLATE ROLLS ARE COMPLETELY CLEAN AND FREE OF DIRT, GRIME, FOREIGN MATTER, AND RAISED METAL PRIOR TO ROLLING. ENSURE THE PANEL BLANKS ARE PROTECTED WITH PLASTIC SHEET DURING THE ENTIRE PROCESS. NOTIFY ENGINEERING (DOUG McCORKLE) PRIOR TO PROCEEDING.	1.00	1.00	1.00	SE121-001P / A	IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
Sub: 26 / Seq: 20 (F)	341-PACIFIC 750 LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS. ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC....	1.00	1.00	1.00	SE121-001P / A				

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A			Engineer BLUE/DOUG MCCORKLE
----------------------	---------	----------	-------------------------------	--	--	--------------------------------

LOAD THE PANEL BLANK (OR CONE) INTO THE DIE SET.
 HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE #_____
 PANEL TO GAGE GAP TOLERANCE: .08" MAX.
 NOTIFY Q/A FOR PROFILE IDC VERIFICATION
 ENSURE THE PANEL MATERIAL EXTENDS BEYOND THE PERIMETER OF THE TRIM-LINES OF THE GAGE BY AT LEAST 1" (TO PROVIDE ADEQUATE STOCK ALLOWANCE FOR RE-POSITIONING, RE-STRIKING, AND ACCURATE TRIMMING).
 Part Number: SE121-001P-2 TEST PANEL
 Part Description: DIE FORMED PANEL

IDC Count : 1 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation Sub: 26 / Seq: 25 (F)	Resource 260-SANDBLAST SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A	
	IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0					

Operation Sub: 26 / Seq: 27 (F)	Resource 230-FABRICATION - WEIDNER INSTALL AND WELD ANNEAL BRACING IN PLACE PER ENGINEERING SKETCH ENSURE PART IS CLEAN AND READY FOR SOLUTION ANNEAL CYCLE	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A	
	IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 1					

Operation Sub: 26 / Seq: 30 (F)	Resource 520-SUBLET, EXOTIC HEAT TREAT SOLUTION ANNEAL FORMED PANEL PER THE FOLLOWING: ATTACH A MINIMUM OF THREE EQUALLY SPACED THERMOCOUPLES TO THE FORMED PANEL CHARGE FURNACE AND HEAT PART UNTIL THERMOCOUPLE READINGS ARE WITHIN 1900 +/-15F. HOLD PART TEMPERATURE AT 1900 DEGREES F. (+/- 15 DEGREES) HOLD FOR 45 MINUTES (+/ 5 MINUTES) RAPID COOL (VIA. WATER QUENCHING OR FORCED AIR CIRCULATION) TO 1000 DEGREES F. OPEN AIR COOL TO AMBIENT TEMP. Specification: AMS2774 Rev: JUL95 Certification: H/T CERTIFICATE Part Number: SE121-001P-2 TEST PANEL Part Description: DIE FORMED PANEL Customer: PPPL Furnace charts: FURNACE CHART	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A	Service ID THRML TR/NA SA
	IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 6 NDT Count: 0 WPS Count: 0					

Operation Sub: 26 / Seq: 32 (F)	Resource 230-FABRICATION - WEIDNER REMOVE ANNEAL BRACING AND PREPARE PANEL FOR RE-STRIKE / FINAL FORMING. ENSURE ALL WELDS ARE COMPLETELY REMOVED AND BLENDED FLUSH AND SMOOTH TO THE BASE MATERIAL. USE CAUTION TO AVOID GOUGES and/or HEAVY SCRATCHES ON THE PANEL SURFACES.	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A	
	IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0					

Operation Sub: 26 / Seq: 35	Resource 805-INPROCESS INSPECTION - PLA	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A	
---------------------------------------	---	-----------------------	-------------------------	----------------------	---	--

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

(F) VISUAL INSPECT SURFACE FOR DAMAGE, PITTING, GOUGES, SCRAPES ETC.....
 NOTIFY ENGINEERING (DOUG McCORKLE) FOR CONCURRENCE
 VERIFY MAGNETIC PERMEABILITY AND RECORD I.D.C. DATA
 Part Number: SE121-001P-2 TEST PANEL
 Part Description: DIE FORMED PANEL

IDC Count : 1 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation Sub: 26 / Seq: 40	Resource 341-PACIFIC 750	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A
---------------------------------------	------------------------------------	-----------------------	-------------------------	----------------------	---

(F) LOAD, ALIGN, AND BOLT DIE SET # _____ INTO THE 750 TON HYDRAULIC PRESS.
 ENSURE THE DIE SET FACES ARE CLEAN AND FREE OF DIRT, OIL, GRIME, FOREIGN MATTER, RAISED OR EMBEDDED MATERIAL, ETC....
 LOAD THE PREFORMED PANEL INTO THE DIE SET.
 "RE-STRIKE" HYDRAULIC FORM THE PANEL TO ACHIEVE THE GEOMETRICAL SHAPE CONFORMING TO INSPECTION GAGE #_____
 PANEL TO GAGE GAP TOLERANCE: .08" MAX.
 VERIFY PROFILE TO INSPECTION GAGE #_____. GAP TOLERANCE: .08" MAX.
 NOTIFY INSPECTOR FOR Q/A IDC VERIFICATION
 LAYOUT AND PRICK-PUNCH TRIM-LINES ON THE PANEL ESTABLISHED FROM THE MACHINED PERIMETER OF THE INSPECTION GAGE.

Part Number: SE121-001P-2 TEST PANEL
 Part Description: DIE FORMED PANEL

IDC Count : 1 Dwg Count: 1 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Operation Sub: 26 / Seq: 50	Resource 260-SANDBLAST	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A
---------------------------------------	----------------------------------	-----------------------	-------------------------	----------------------	---

(F) SHOT BLAST THE ENTIRE PANEL 100% USING 180-220 GRIT VIRGIN ALUMINUM OXIDE MEDIA TO REMOVE ANY RESIDUE FROM THE FORMING PROCESS.

IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation Sub: 26 / Seq: 60	Resource 230-FABRICATION - WEIDNER	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A
---------------------------------------	--	-----------------------	-------------------------	----------------------	---

(F) TRIM PERIMETER TO PROVIDED TRIM-LINES. NOTE THAT INSTALLING THE WELD PREP IS NOT REQUIRED AT THIS STAGE (ADDITIONAL FITTING / TRIMMING MAY BE REQUIRED AT INSTALLATION)
 SAND AND POLISH THE INSIDE SURFACE 100% TO ACHIEVE A 32 MICRO SURFACE FINISH (WITH THE EXCEPTION OF THE WELDING / TRIMMING ZONES).
 CLEAN PANEL PER CLEANING PROCEDURE PP475.
 SPLIT THE PANEL TO SIMULATE PRODUCTION WELD JOINT(S).
 PREP, FIT AND WELD JOINTS TO DEVELOP WELDING SEQUENCES AND MINIMIZE WELDING DISTORTION. ENSURE THE PART IS RESTRAINED IN A MANNER SIMULATING PRODUCTION THROUGHOUT THE WELDING PROCESS.
 CWI VISUAL INSPECT WELDS 100% UNDER 8X MAGNIFICATION PER ASME CODE ARTICLE 6, SECTION V. ACCEPTANCE PER AWS D1.6, 6.29.1. NO CERTIFICATE REQUIRED. THIS IS A TEST PIECE.
 REVIEW RESULTS WITH ENGINEERING (DOUG McCORKLE)

IDC Count : 0 Dwg Count: 1 Pgm Count: 0 QAP Count: 0 NDT Count: 0 WPS Count: 0

Operation Sub: 26 / Seq: 70	Resource 805-INPROCESS INSPECTION - PLA	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121-001P / A
---------------------------------------	---	-----------------------	-------------------------	----------------------	---

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

(F) VERIFY PROFILE TO INSPECTION GAGE #_____. GAP TOLERANCE: .08" MAX. PERIMETER SHOULD FALL WITHIN .03" OF GAGE PERIMETER.
INSPECT AND RECORD INTERIOR SIDE SURFACE FINISH.
INSPECT AND RECORD MAGNETIC PERMEABILITY.
Test Certification: DIMENSIONAL INSPECTION MAP Rev:
Part Number: SE121-001P-2 TEST PANEL
Part Description: DIE FORMED PANEL

IDC Count : 3 Dwg Count: 1 Pgm Count: 0 QAP Count: 3 NDT Count: 0 WPS Count: 0

Sub ID 30	Part ID PQR PROCESS	Qty 1	Drawing ID / Rev / Parent Sub:26 Op:60
---------------------	-------------------------------	-----------------	---

Operation Sub: 30 / Seq: 10 (R)	Resource 410-BURNOUT TABLE BURN OUT TWO TEST PLATES 6 X 15 AND CLEANUP. NOTIFY WELDING ENGINEERING WHEN PARTS ARE AVAILABLE	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev	QAP Count: 2	NDT Count: 0	WPS Count: 0
	IDC Count : 0	Dwg Count: 0	Pgm Count: 0					

Piece # 10 (C)	Part ID INCONEL 625_5-PLATE,NICKEL ALLOY .375" THK Vendor Part ID: INCONEL 625_5 INCONEL 625 (UNS N06625) PER ASTM B 443-00 ANNEALED MAGNETIC PERMEABILITY SHALL NOT EXCEED 1.00 (REF. ASTM A800). SURFACE MUST BE PROTECTED FROM CONTACT WITH IRON AND IRON ALLOY MATERIALS CERTS & MILL TEST REPORTS REQ'D WITH SHIPMENT.	Qty 338.3	Drawing ID / Rev	Vendor 1810	Dimensions 15.375*22
-----------------------------	---	---------------------	-------------------------	-----------------------	--------------------------------

Operation Sub: 30 / Seq: 20 (R)	Resource 230-FABRICATION - WEIDNER WELD PQR PLATE PER WELDING ENGINEERING DIRECTION.	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev	QAP Count: 0	NDT Count: 0	WPS Count: 0
	IDC Count : 0	Dwg Count: 0	Pgm Count: 0					

Sub ID 19	Part ID SE121 PORT SUB-ASSEMBLY	Qty 1	Drawing ID / Rev / Parent Sub:1 Op:70
---------------------	---	-----------------	--

Operation Sub: 19 / Seq: 10 (F)	Resource 230-FABRICATION - WEIDNER INSTALL AND WELD CONFLAT FLANGE TO TUBE PER DRAWING. FIT AND TRIM THE LENGTH FOR INSTALLATION (USE REFERENCE SCRIBE LINES ON BUILD FIXTURE). PREP FOR WELDING IN PLACE. GRIND / BLEND THE INTERIOR WELD SMOOTH. POLISH THE ENTIRE INSIDE SURFACE SMOOTH TO ACHIEVE A 32 MICRO SURFACE FINISH. CLEAN THE INTERIOR SURFACES PER PP475	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121 / A	QAP Count: 0	NDT Count: 0	WPS Count: 1
	IDC Count : 0	Dwg Count: 0	Pgm Count: 0					

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

Operation Sub: 19 / Seq: 20 (F)	Resource 805-INPROCESS INSPECTION - PLA INSPECT THE INTERIOR SURFACE FINISH OF THE PORT SUB-ASSY. INSPECT THE MAGNETIC PERMEABILITY OF THE PORT EXTENSION TO FLANGE WELD AND SURROUNDING AREA. RECORD IDC DATA Part Number: SE212-003P-3 Part Description: PORT EXTENSION Customer: PPPL	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121 / A
--	--	-----------------------	-------------------------	----------------------	--------------------------------------

IDC Count : 2 Dwg Count: 0 Pgm Count: 0 QAP Count: 3 NDT Count: 0 WPS Count: 0

Sub ID 20	Part ID CONFLAT FLANGE	Qty 1	Drawing ID / Rev / Parent Sub:19 Op:10
---------------------	----------------------------------	-----------------	---

Operation Sub: 20 / Seq: 10 (R)	Resource 820-RECEIVING INSPECTION RECEIVING INSPECTION RECEIVE AND INSPECT THE FOLLOWING PARTS: (THEY SHOULD ALL ARRIVE TOGETHER) F10000000NC4 FG1000CI FG1000VU FB1000C12S GC0275S CONTACT ENGINEERING (DOUG MCCORKLE) WHEN PARTS ARRIVE.	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121 / A
--	---	-----------------------	-------------------------	----------------------	--------------------------------------

IDC N/A IDC Count : 0 Dwg Count: 0 Pgm Count: 0 QAP Count: 2 NDT Count: 0 WPS Count: 0

Piece # 10 (R)	Part ID F10000000NC4-FLANGE, CONFLAT, NON-ROTATE, 10.00" FLANGE, CONFLAT, NON-ROTATABLE 10.00 X BLANK X 0.97", CLEAR BOLT HOLES, 304L	Qty 1.0	Drawing ID / Rev	Vendor	Dimensions
	Material Certification: Part Number: F10000000NC4				

Piece # 20 (R)	Part ID FG1000CI-GASKET KIT (10/PK), COPPER, FOR 10" CFF GASKET KIT (10/PACK), COPPER, INDIVIDUAL SEAL, FOR 10" CONFLAT FLANGE VARIAN VACUUM TECHNOLOGIES	Qty 1.0	Drawing ID / Rev	Vendor	Dimensions
	Material Certification: Part Number: FG1000CI				

Piece # 30 (R)	Part ID FG1000VU-GASKET, VITON, FOR 10" CFF GASKET, VITON, FOR 10" CONFLAT FLANGE	Qty 1.0	Drawing ID / Rev	Vendor	Dimensions
-----------------------------	--	-------------------	-------------------------	---------------	-------------------

Workorder: 64880/1 Part ID: Qty: 1 Drawing ID / Rev: SE121 / A Engineer: BLUE/DOUG MCCORKLE

VARIAN VACUUM TECHNOLOGIES

Material Certification:
Part Number: FG1000VU

Piece #	Part ID	Qty	Drawing ID / Rev	Vendor	Dimensions
40	FB1000C12S-BOLT AND NUT KIT, 12 PT, SILVER PLATED	1.0			
(R)	BOLT AND NUT KIT (25/PACK), 12 POINT, ASTM A193 GR. B8 SILVER PLATED, FOR 10" CONFLAT FLANGE VARIAN VACUUM TECHNOLOGIES				

Material Certification:
Part Number: FB1000C12S

Piece #	Part ID	Qty	Drawing ID / Rev	Vendor	Dimensions
50	GC0275S-GASKET CLIP KIT (10/PK), FOR 10" CFF	1.0			
(R)	GASKET CLIP KIT (10/PACK) FOR 10" CONFLAT FLANGE VARIAN VACUUM TECHNOLOGIES				

Material Certification:
Part Number: GC0275S

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev						
Sub: 20 / Seq: 20 (R)	108-TOOL ROOM - PLANT 1 DRILL / TAP 1/2" NPT THREAD FOR VACUUM TESTING. SPOTFACE, DRILL / REAM FOR 1/2" TOOLING BALL IN THE CENTER OF THE FLANGE. (PROCESS DRAWING NEEDED)	1.00	1.00	1.00		IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 0

Sub ID	Part ID	Qty	Drawing ID / Rev
21	PORT EXTENSION TUBE	1	/
Parent Sub:19 Op:10			

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev						
Sub: 21 / Seq: 10 (C)	230-FABRICATION - WEIDNER INSPECT DIAMETERS AND LENGTH RECORD IDC INFORMATION NOTIFY ENGINEERING (DOUG McCORKLE) OF RESULTS WELD / BLEND MIS-ALIGNMENT OF MANUFACTURERS WELDS POLISH THE ENTIRE INSIDE SURFACE TO A 32 MICRO-INCH SURFACE FINISH. LAYOUT ONE AND CUT ONE END SQUARE FOR FLANGE INSTALLATION (REMOVE MINIMAL MATERIAL FOR LATER INSTALLATION 16" MINIMUM LENGTH)	1.00	1.00	1.00	SE121 / A	IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 3	NDT Count: 0	WPS Count: 1

Piece #	Part ID	Qty	Drawing ID / Rev	Vendor	Dimensions
10	SE121-001P-5-INCO 625 TUBE 8.0" OD X .12" WA. X 18.0"	1.0		5647	

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

(C) Vendor Part ID: SE121-001P-5
 TUBE, ROUND, INCONEL 625, SEAMLESS OR WELDED. ASTM B444 OR ASTM B705
 MTM AUTHORIZATION OF WELDING PROCEDURE REQUIRED PRIOR TO STARTING WORK.
 NOTE THAT THE FOLLOWING REQUIREMENTS WILL BE PERFORMED / TESTED BY MAJOR TOOL & MACHINE AFTER DELIVERY. ALL EFFORTS TO ACCOMODATE / ENSURE SUCESS MUST BE MAINTAINED:
 MAGNETIC PERMEABILITY REQUIREMENT: 1.01 MAX.
 VACUUM INTEGRITY REQUIREMENT: TOTAL HELIUM LEAK RATE FOR THE TUBE SHALL BE LESS THAN OR EQUAL TO 1.7 X 10(-9) TORR-L/S
 INTERIOR SURFACE FINISH REQUIREMENT: INTERIOR WELD BEADS WILL BE GROUND FLUSH. THE ENTIRE INTERIOR SURFACE WILL BE POLISHED TO A 32 MICRO SURFACE FINISH AND VERIFIED PER ASME B46.1.
 EXTERIOR SURFACE FINISH: MILL SURFACE ACCEPTABLE. NO PITS, SCRAPES OR GOUGES.
 MATERIAL CERTIFICATION AND TEST REPORTS REQ'D WITH SHIPMENT.

Sub ID 29	Part ID PORT EXTENSION TUBE (TAKE 2)	Qty 1	Drawing ID / Rev /	
Parent Sub:19 Op:10				

Operation Sub: 29 / Seq: 10 (F)	Resource 805-INPROCESS INSPECTION - PLA PRIOR TO CUTTING / FORMING, INSPECT AND RECORD THE MAGNETIC PERMEABILITY OF THE SHEET (COORDINATE WITH MATERIALS DEPT. AND INSPECT THE APPROXIMATE PART ENVELOPE WITHIN THE STOCK SHEET) Part Number: SE121-001P-3 Part Description: PVVS PORT EXTENSION TUBE	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev SE121 / --				
	IDC Count : 1	Dwg Count: 0	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0			

Operation Sub: 29 / Seq: 20 (F)	Resource 415-ROLLING/SHEAR/BRAKE PRESS 1. SHEAR RECTANGLE PER MATERIAL CARD DIMENSIONS 2. ROLL TO 8" O.D. +/-0.03" X 20" LONG. LEAVE TRIM STOCK OVERLAPPED (FABRICATOR WILL TRIM). ENSURE OVERLAP IS ADEQUATE TO TRIM AND FIT THE DIAMETER REMOVING ANY ROLL FLATS RESULTANT FROM STARTING AND FINISHING THE ROLLING SEQUENCE. 3. NOTIFY Q/A FOR DIMENSIONAL / MAGNETIC PERMEABILITY VERIFICATION.	QtyPer 1.00	StartQty 1.00	EndQt 1.00	Drawing ID / Rev				
	IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 3	NDT Count: 0	WPS Count: 0			

Piece # 10 (F)	Part ID INCONEL 625_660-SHEET,NICKEL ALLOY .125" THK INCONEL 625 SHEET, .125" THICK PER AMS 5599 / ASTM B443 (UNS N06625). CERT AND MILL TEST REPORT REQ'D WITH SHIPMENT.	Qty 760.0	Drawing ID / Rev	Vendor	Dimensions 20*38
	Material Certification: Part Number: SE121-001P-3 Part Description: PORT EXTENSION TUBE				

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev				
------------------	-----------------	---------------	-----------------	--------------	-------------------------	--	--	--	--

MTTRAVLR.qrp W:64880/1-0/Inc Matl/Inc Legs

Workorder	Part ID	Qty	Drawing ID / Rev	Engineer						
64880/1		1	SE121 / A	BLUE/DOUG MCCORKLE						
Sub: 29 / Seq: 30 (F)	805-INPROCESS INSPECTION - PLA INSPECT AND RECORD MAGNETIC PERMEABILITY (AFTER ROLLING) Part Number: SE121-001P-3 Part Description: PVVS PORT EXTENSION TUBE	1.00	1.00	1.00	SE121 / --					
		IDC Count : 1	Dwg Count: 0	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0			
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev					
Sub: 29 / Seq: 40 (F)	230-FABRICATION - WEIDNER TRIM, FIT, (PURGE WELD JOINT WITH 100% ARGON. PURGE DAM MATERIAL MUST BE MADE FROM EITHER 625 INCONEL OR 300 SERIES STAINLESS STEEL) AND TACK WELD INTO 8" O.D. TUBE. PREPARE FOR PLASMA ARC WELDING	1.00	1.00	1.00	SE11 / --					
		IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 1			
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev					
Sub: 29 / Seq: 50 (F)	205-PLASMA WORKCENTER SETUP, PURGE WELD JOINT WITH 100% ARGON. PURGE DAM MATERIAL MUST BE MADE FROM EITHER 625 INCONEL OR 300 SERIES STAINLESS STEEL, AND PLASMA ARC WELD THE JOINT PER DRAWING.	1.00	1.00	1.00	SE121 / --					
		IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 1			
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev					
Sub: 29 / Seq: 60 (F)	230-FABRICATION - WEIDNER BLEND THE INTERIOR WELD SURFACE FLUSH TO THE BASE MATERIAL. POLISH THE ENTIRE INTERIOR OF THE TUBE TO ACHIEVE A 32 MICRO-INCH RA SURFACE FINISH.	1.00	1.00	1.00	SE121 / --					
		IDC Count : 0	Dwg Count: 0	Pgm Count: 0	QAP Count: 0	NDT Count: 0	WPS Count: 1			
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev					
Sub: 29 / Seq: 70 (F)	805-INPROCESS INSPECTION - PLA INSPECT DIAMETER, ROUNDNESS, WELDING DISTORTION, MAGNETIC PERMEABILITY, AND INTERIOR SURFACE FINISH. RECORD IDC DATA Part Number: SE121-001P-3 Part Description: PVVS PORT EXTENSION TUBE	1.00	1.00	1.00	SE121 / --					
		IDC Count : 2	Dwg Count: 0	Pgm Count: 0	QAP Count: 2	NDT Count: 0	WPS Count: 0			
Sub ID	Part ID	Qty	Drawing ID / Rev							
25	PORT EXTENSION WELD BACKING RI	1	/	Parent Sub:1 Op:90						
Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev					
Sub: 25 / Seq: 10 (F)	415-ROLLING/SHEAR/BRAKE PRESS 1. SHEAR STRIP PER MATERIAL CARD AND DEBURR. 2. ROLL THE EASY WAY TO A 8.093" I.D. OBJ (0.031" WELD SHRINKAGE ALLOWANCE).	1.00	1.00	1.00	SE121-003P / 0					
		IDC Count : 0	Dwg Count: 1	Pgm Count: 0	QAP Count: 3	NDT Count: 0	WPS Count: 0			
Piece #	Part ID	Qty	Drawing ID / Rev	Vendor	Dimensions					
10	INCONEL 625_660-SHEET,NICKEL ALLOY .125" THK	162.0			4.5*36					

Workorder 64880/1	Part ID	Qty 1	Drawing ID / Rev SE121 / A	Engineer BLUE/DOUG MCCORKLE
-----------------------------	----------------	-----------------	--------------------------------------	---------------------------------------

(F) INCONEL 625 SHEET, .125" THICK PER
AMS 5599 / ASTM B443 (UNS N06625).
CERT AND MILL TEST REPORT REQ'D WITH SHIPMENT.

Material Certification:
Part Number: SE121-003P-4
Part Description: WELD BACKING RING

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	IDC Count	Dwg Count	Pgm Count	QAP Count	NDT Count	WPS Count
Sub: 25 / Seq: 20 (F)	230-FABRICATION - WEIDNER 1. TRIM AND FIT TO VESSEL CONTOUR, CUT WIDTH, PREP 2. WELD PER DRAWING (SIZE TO EXISTING PORT TUBE) 3. BLEND WELD FLUSH TO BASE METAL	1.00	1.00	1.00	SE121-003P / 0	0	1	0	0	0	1

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	IDC Count	Dwg Count	Pgm Count	QAP Count	NDT Count	WPS Count
Sub: 25 / Seq: 30 (F)	415-ROLLING/SHEAR/BRAKE PRESS RE-ROLL / ROUND UP BAND (IF NECESSARY)	1.00	1.00	1.00	SE121 / A	0	0	0	0	0	0

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	IDC Count	Dwg Count	Pgm Count	QAP Count	NDT Count	WPS Count
Sub: 25 / Seq: 40 (F)	805-INPROCESS INSPECTION - PLA VERIFY MAGNETIC PERMEABILITY. RECORD I.D.C. DATA Part Number: PVVS PORT EXTENSION TUBE	1.00	1.00	1.00	SE121 / A	1	0	0	1	0	0

Sub ID	Part ID	Qty	Drawing ID / Rev
28	STORAGE / SHIPPING CRATE	1	/
Parent Sub:1 Op:115			

Operation	Resource	QtyPer	StartQty	EndQt	Drawing ID / Rev	IDC Count	Dwg Count	Pgm Count	QAP Count	NDT Count	WPS Count
Sub: 28 / Seq: 10 (F)	425-SHIPPING - PLANTS 1 & 2 BUILD STORAGE / SHIPPING CRATE PER ENGINEERING DRAWING	1.00	1.00	1.00	SE121 / A	0	0	0	0	0	0