

NCSX Fabrication Project
Work Breakdown Structure (WBS) Dictionary
Diagnostic Systems (WBS 3)

Revision 0

September 8, 2003

Prepared by:

R. Simmons, Systems Engineering Support Manager

Reviewed by:

D. Johnson, WBS 3 Manager

L. Dudek, Ancillary Systems Project
Engineer

R. Strykowski, Project Control
Manager

M. Zarnstorff, NCSX Physics Manager

W. Reiersen, Engineering
Manager

Approved by:

G.H. Neilson, Project Manager

NCSX WBS Dictionary

Diagnostic Systems

WBS Element: 3	WBS Level: 2
WBS Title:	Diagnostic Systems
Description:	<p>NCSX operations are divided into six phases:</p> <ol style="list-style-type: none"> 1. Initial Operation 2. Field Line Mapping 3. Initial Ohmic 4. Initial Auxiliary Heating 5. Confinement and Beta Push 6. Long Pulse <p>The NCSX Fabrication Project includes all diagnostic equipment required through the Field Line Mapping of operation (that is, Phases 1 and 2).</p> <p>Included in the Fabrication Project are all the engineering and physics design efforts starting with the preliminary design phase (Title I) and ending with completion of the Fabrication Project, all the necessary Research and Development (R&D) to support the design effort, all component fabrication, assembly, and installation activities, and all system level commissioning and testing, including diagnostic alignments and calibrations.</p> <p>This summary-level WBS element consists of plasma diagnostic subsystems and components to provide the capability to measure the performance of the NCSX device.</p> <p>Diagnostic Systems (WBS 3) include:</p> <ul style="list-style-type: none"> • Magnetic Diagnostics (WBS 31); • Fast Particle Diagnostics (WBS 32); • Impurity Diagnostics (WBS 33); • MHD Diagnostics (WBS 34); • Profile Diagnostics (WBS 35); • Edge and Divertor Diagnostics (WBS 36); • Turbulence Diagnostics (WBS 37); • EB Mapping Diagnostics (WBS 38); and • Diagnostics Integration (WBS 39). <p>The measurement requirements that the diagnostics must satisfy are derived from the research program. The diagnostics for the first 2 phases are meant to satisfy the experimental needs of the research program planned for these periods.</p>

NCSX WBS Dictionary

Diagnostic Systems

WBS Element: 31		WBS Level: 3
WBS Title:	Magnetic Diagnostics	
Description:	<p>This WBS element consists of all the magnetic diagnostics required to accomplish the NCSX mission as defined in the General Requirements Document. This includes in-vessel and ex-vessel magnetic sensors needed to measure the equilibrium plasma position and shape, the plasma current, the plasma conductivity, and the total plasma stored energy. It also includes sensors to measure edge magnetic field variations due to internal MHD activity (Mirnov coils). For a typical group of magnetics channels, there are the sensors, sensor mounts, sensor lead cables, a vacuum electrical feed-thrus (if in-vessel sensors), junction boxes near the machine, field cables, racks, rack cross-connects, interconnect rack cabling, integrators, data acquisition, AC power and isolation and grounding digitizers. WBS 3 is responsible for the sensors, sensor mounts, sensor leads, racks, and integrators. Other components in the above list are covered in other WBS areas.</p> <p>For Phases 1 and 2, an extensive set of ex-vessel sensors will be installed, and a few of them will be connected to field cables, integrators and digitizers.</p> <p>A significant modeling development is needed to optimally plan the type, number and placement of magnetic sensors, particularly those needed for plasma control. The model development is not budgeted in this WBS.</p>	

WBS Element: 32		WBS Level: 3
WBS Title:	Fast Particle Diagnostics	
Description:	<p>This WBS element consists diagnostics required for evaluation of fast particle behavior on NCSX. Fast particles include confined and escaping beam ions and fusion products, as well as escaping fast neutrals. There are no diagnostics in this area needed for before initial NBI operation. This WBS is responsible for the vacuum interface that might include shutters or valves, pumping systems for possible vacuum extensions, the mechanical support structures, the sensors, the racks, and sensor specific electronics. Other WBS units are responsible for field cabling, rack terminal blocks, rack AC power and grounding, and data acquisition hardware.</p>	

NCSX WBS Dictionary

Diagnostic Systems

WBS Element: 33		WBS Level: 3
WBS Title:	Impurity Diagnostics	
Description:	<p>This WBS element consists of all diagnostics required for measurement of the types and concentrations of impurities in the NCSX plasmas. Since plasma performance typically degrades with increasing amounts of impurities, such diagnostics help to assess the readiness of the machine for experiments, most of which require good performance. They provide critical information supporting decisions on whether to use wall conditioning procedures, like bake-out and glow discharge cleaning, to reduce impurities. They also provide early warning on problems with the plasma facing components, with air leaks, etc. These diagnostics typically consist of a vacuum interface providing the view for an array of sightlines through the plasma, optics (in some case pinhole optics) for imaging the light, fiber optical cables, to relay the light to sensors, dispersive elements to analyze particular wavelengths, detectors and electronics to convert the light signal to a voltage, and associated data acquisition electronics and digitizers. If vacuum windows are used, shutters will be needed to prevent coating during wall conditioning procedures. This WBS is responsible for the vacuum interface, the shutters, the collection optics and associated support system, the fiber optics, the spectrometers, as well as the detectors and associated electronics and rack. Other WBS units are responsible for field cabling, rack terminal blocks, rack AC power and grounding, and data acquisition hardware. For Phases 1 and 2, there are no diagnostics planned in this category.</p>	

WBS Element: 34		WBS Level: 3
WBS Title:	MHD Diagnostics	
Description:	<p>This WBS element consists of all MHD diagnostics (excluding low frequency Mirnov coils which are part of WBS 31 which are also used for plasma control) required to characterize MHD activity, magnetic island locations and widths, and disruptions. A variety of diagnostic techniques will be used. This WBS is responsible for the vacuum interface, including windows, shutters, valves or electrical feed-thrus. Responsibility also includes sensors, mounting structures and sensor cabling near the vacuum vessel. Sensor electronics and racks are also included. Other WBS units are responsible for field cabling, rack terminal blocks, rack AC power and grounding, and data acquisition hardware. . For Phases 1 and 2, there are no diagnostics planned in this category.</p>	

NCSX WBS Dictionary

Diagnostic Systems

WBS Element: 35		WBS Level: 3
WBS Title:	Profile Diagnostics	
Description:	<p>This WBS element covers diagnostics required to provide spatial profile information at several times, typically every 5-10 msec, for electron density and electron and ion temperature, for the magnetic field direction, and for the toroidal and poloidal rotation. These kinetic profiles provide the information needed characterize and understand local transport and stability issues.</p> <p>A variety of diagnostic techniques will be used. This WBS is responsible for the vacuum interface, including windows, shutters, valves or electrical feed-thrus. Responsibility also includes sensors, mounting structures and sensor cabling near the vacuum vessel. Sensor electronics and racks are also included. Other WBS units are responsible for field cabling, rack terminal blocks, rack AC power and grounding, and data acquisition hardware. Some of the techniques may require active probing with a laser beam or diagnostic neutral beam. These active probes are also the responsibility of this WBS.</p> <p>For Phases 1 and 2, there are no diagnostics planned in this category.</p>	

WBS Element: 36		WBS Level: 3
WBS Title:	Edge and Divertor Diagnostics	
Description:	<p>This WBS element consists of diagnostics required to characterize the plasma edge and divertor regions. Quantities measured include the hydrogen recycling, the edge neutral pressure, the edge temperature and density profiles, the divertor radiated power, the divertor target temperature, and edge and divertor flows. This information is important in the understanding of edge transport and plasma wall interactions. A variety of diagnostic techniques will be used. This WBS is responsible for the vacuum interface, including windows, shutters, valves or electrical feedthrus. Responsibility also includes sensors, mounting structures and sensor cabling near the vacuum vessel. Sensor electronics and racks are also included. Other WBS units are responsible for field cabling and junction boxes, rack terminal blocks, rack AC power and grounding, and data acquisition hardware.</p> <p>For Phases 1 and 2, an initial implementation of a fast TV camera is planned in this category.</p>	

NCSX WBS Dictionary

Diagnostic Systems

WBS Element: 37		WBS Level: 3
WBS Title:	Turbulence Diagnostics	
Description:	<p>This WBS element consists of diagnostics required to measure plasma turbulence, which causes increased energy and particle transport. Turbulence phenomena in both the plasma core and edge regions can significantly influence plasma performance. Data from these diagnostics, combined with data from the kinetic profile diagnostics, will be critical in the understanding of the details of plasma loss mechanisms. This WBS is responsible for the vacuum interface, including windows, shutters, valves or electrical feedthrus. Responsibility also includes sensors, mounting structures and sensor cabling near the vacuum vessel. Sensor electronics and racks are also included. Other WBS units are responsible for field cabling and junction boxes, rack terminal blocks, rack AC power and grounding, and data acquisition hardware.</p> <p>For Phases 1 and 2, there are no diagnostics planned in this category.</p>	

WBS Element: 38		WBS Level: 3
WBS Title:	Electron Beam (EB) Mapping	
Description:	<p>This WBS element consists of all EB mapping equipment required to accomplish the NCSX mission as defined in the General Requirements. This equipment will be required in the field-line mapping phase of operations (Phase 2) and thus is included in the Fabrication Project.</p> <p>The field line mapping hardware consists of a probe drive with an electron gun at its tip, which can be accurately positioned along a line through the nominal cross-section. The axis of the gun also needs to be adjustable for alignment with the local field. During field mapping the electron beam from the gun will intercept a phosphor coated mesh. The light from the strike points will be imaged by a high resolution CCD camera. Careful metrology will reference positions to machine coordinates. Strike points will be compared to expectations of a code, which will compute the beam trajectory for given coil currents. Magnetic island structures will be investigated for different vacuum field configurations.</p>	

WBS Element: 39		WBS Level: 3
WBS Title:	Diagnostics Integration	
Description:	<p>This WBS element consists of the physics support to provide diagnostic input through the detailed design phase of the machine. It also includes engineering support required to integrate the Diagnostic Systems (WBS 3) with the NCSX facility. This continues through machine assembly phase and as the baseline diagnostics are being developed.</p>	