NCSX June 2007 ETC TABLE IV - Uncertainty of Estimate and Residual Risk Assessment

WBS Number: 163

WBS Title: Coil Protection Systems

Job Number: 1601-163

Job Title: Coil Protection Systems Interfaces

Job Manager: Paul Goranson

Uncertainty of the Estimate

Uncertainty

Range (%)

Comments/Other Considerations

High Х

Medium Low

Χ

Design well established based on previous devices

-5%/+10%

Standard Components

Design Complexity Other Comments:

Design Maturity

Note: High/Medium/Low uncertainty assessment from Job Manager. Uncertainty range based on AACEI recommended practice 18R-97 as amended for NCSX.

Residual Impacts	<u>s</u>								
				Cost Impact Schedule Impact					
		Likelihood of							
Job	Risk Description	Occurring	Mitigation Plan	Basis of estimate	Low	High	Low	High	

NONE

Notes:

- Low cost and schedule impacts are considered the minimum (0-percentile) impacts should the event occur. High cost and schedule impacts are considered the maximum (100-percentile) impacts should the event occur
- Cost impacts should be entered as man-hours (by demographic) and M&S direct cost under basis of estimate. Cost impacts should NOT include standing army costs which are separately calculated from the schedule impact Project control is reponsible for quantifying the low and high cost impacts based on the labor hours and M&S identified
- The schedule impacts should be entered as the min and max impacts on the critical path.
- If there is no critical path impact then the schedule entries should be zero.
- Likelihood of occurrence should be entered consistent with our risk classification methodology, i.e. VL= Very Likely (P>80%), L=Likely (80%>P>40%), U=Unlikley (40%>P>10%), VU=Very Unlikely (P<10%), NC=Non-credible (P<1%)